



PDU20BHVIEC12Ra

BASIC PDU



Engineered to distribute UPS, generator or utility AC power to equipment.

The CyberPower PDU20BHVIEC12Ra, a 12-outlet (rear) rackmount basic power distribution unit (PDU), provides 200V/230V 20A output. It distributes power to ten IEC-320 C13, two IEC-320 C19 receptacles from a IEC-320 C20 plug. Designed for datacenters and other electrically demanding applications, the PDU20BHVIEC12Ra has rugged, industrial-grade metal housing and a ten-foot AC power cord. It can be mounted either horizontally or vertically, includes a cord retention tray, and is ETL/RoHS certified. A limited lifetime warranty covers defects in materials and workmanship in the product under normal use and conditions.

TYPICAL APPLICATIONS

- VoIP Phone Systems
- Network Closets
- Data Centers
- Industrial Environments

FEATURES

- Phase: Single
- Amps: 20A (Derated to 16A)
- Volts: 200 - 230 V
- Frequency: 50Hz/60Hz
- Plug type: IEC-320 C20
- Outlets: 10 x IEC-320 C13, 2 x IEC-320 C19
- Size: 1U Rackmount
- Dimensions (in.): 17.5W x 1.75H x 1.5D
- Cord length (ft.): 10
- Warranty: Limited Lifetime

SPECIFICATIONS

INPUT	
Cord Length (ft.)	10 ft (3.0 m)
Input Plug Type	IEC-320 C20
Maximum Input Current	20 A

OUTPUT	
Nominal Output Voltage	200 - 230 VAC
Outlet Type	10 x IEC-320 C13 2 x IEC-320 C19
Outlets - Front	0
Outlets - Rear	12
Outlets - Total	12
Overload Protection	20 A

PDU20BHVIEC12Ra

BASIC PDU



SPECIFICATIONS

PHYSICAL	
Color	Black
Form Factors Supported	1U Rackmount 0U Vertical Rackmount Undercounter Installation Supported
Material of Construction	Metal
Rack Height	1U
PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	44.45 x 4.45 x 3.81 cm
Physical Dimensions - Width/Height/Depth (mm)	445 x 44 x 38 mm
Physical Dimensions - Width/Height/Depth (in.)	17.5 x 1.75 x 1.5 in.
Weight (kg)	0.91 kg
Weight (lbs.)	2.0 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	15.24 x 7.62 x 46.99 cm
Shipping Dimensions - Width/Height/Depth (mm)	152.4 x 76.2 x 469.9 mm
Shipping Dimensions - Width/Height/Depth (in.)	6.0 x 3.0 x 18.5 in.
Shipping Weight (kg)	0.91 kg
Shipping Weight (lbs.)	2.0 lbs.
ENVIRONMENTAL	
Operating Elevation	0 - 10,000 ft (0 - 3,048 m)
Operating Relative Humidity	0 - 95% (non-condensing)
Operating Temperature	32 - 95 °F (0 - 35 °C)
Storage Elevation	0 - 50,000 ft (0 - 15,239 m)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	ETL (test followed UL 60950-1)
WARRANTY	
Product Warranty	Limited Lifetime Warranty