



By GAI-Tronics
Catalog # [540-001](#)

The Model 540-001 LED Strobe features an integral LED tower with constant-on and flashing operations. In addition, the LED strobe provides a secondary contact output for activation of external auxiliary equipment. The Model 540-001 LED Strobe is specifically designed to operate with all GAI-TRONICS' emergency and SMART telephones, providing 240 flashes per minute when the telephone is in use. GAI-TRONICS' emergency telephones are typically installed in many types of public areas such as, college campuses, parking garages, shopping malls, hospitals, sports arenas, amusement parks and more.

Features

- High Visibility, Even in Daylight
- Low Power Consumption (.39 Amperes)
- UL Listed for Outdoor Wet Locations
- Low Operating Temperature
- 240 Flashes Per Minute
- UL/cUL Listed
- Dry Contact Closure Output
- 120 V ac Input

General

Catalog Number	540-001
UPC	850025795050
Weather Rating	UL "Outdoor Wet" Locations

Dimensions



Height	7 in
Width	6.5 in

Certifications And Compliance

Certified Listed	UL 1638 / CSA C22.2 No. 205-12
------------------	--------------------------------

Product Assets

- [Installation Manuals - Model 540-001 LED Strobe with Constant-On Feature](#)
- [Installation Manuals - Model 4115A Surface-Mount Strobe Mounting Bracket Assembly](#)
- [Literature - LED Strobe with 4115A Surface-Mount Strobe Mounting Bracket Assembly](#)
- [Sales Drawings - Strobe Mounting Details - 4115A](#)
- [Specifications - 540001](#)