

Specifications



Photo is representative



Eaton LBI215

Eaton Cooper Power series loadbreak bushing insert, EPDM rubber, 15 kV, Phase to ground: 8.3 kV, AC 1 min: 34 kV, DC 15 min: 53 kV, BIL: 95 kV, Corona: 11 kV, 200 A, Bulk pack 30

General specifications

PRODUCT NAME	Eaton Cooper Power series loadbreak bushing insert
CATALOG NUMBER	LBI215
UPC	194006006064
PRODUCT HEIGHT	7.24 in
PRODUCT DIAMETER	3 in
PRODUCT WEIGHT	1.1 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std 386



Powering Business Worldwide

Product specifications	
TYPE	Loadbreak bushing insert
AC 1 MINUTE VOLTAGE WITHSTAND	34 kV
BASIC IMPULSE LEVEL	95 kV
CURRENT RATING	200 A
DC 15 MINUTE WITHSTAND	53 kV
MATERIAL	EPDM rubber
MAXIMUM RATING PHASE-TO-GROUND	8.3 kV
CORONA VOLTAGE LEVEL - MIN	11 kV
STANDARD VOLTAGE CLASS	15 kV
PACKAGING	Bulk pack 30

Resources	
CATALOGS	200 A 15 kV class loadbreak bushing insert
INSTALLATION INSTRUCTIONS	200 A, 15 and 25 kV class loadbreak bushing insert installation instructions
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - LBI215 Line installation and protective equipment specifiers guide

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

