

SONANCE

POWERPIPE X SERIES DATA SHEET

PPX12

TECHNICAL SPECIFICATIONS

SKU	93787 - Each
Woofers	12" (305mm) anodized aluminum cone, rubber surround, high excursion
Frequency Response	34Hz - 100Hz +/-3dB
Impedance	4 ohms nominal
Sensitivity (2.83V/1m)	93dB SPL
Enclosure	MDF (Medium Density Fiberboard)
Finish	Textured Black
Recommended Power	500 watts
Recommended Amplifiers	Blaze Powerzone Connect 1502 3004 6008 Sonance DSP 2-750 MKIII
Tube Inside Diameter	5.98" (152mm)
Tube Length	25.59" (650mm)
Product Dims w/ Feet (WxHxD)	15.75" x 16.36" x 15.16" (400mm x 415mm x 385mm)
Product Dims w/o Feet (WxHxD)	15.75" x 15.75" x 15.16" (400mm x 400mm x 385mm)
Product Weight	55.87 lbs. (25.34kg)
Shipping Weight	64.37 lbs. (29.2kg) Team lift required

ACCESSORIES

PPX-8R | 93796

PPX 8" XPC Grille Connector

PPX-6R | 93795

PPX 6" XPC Grille Connector

PPX-6-90 | 93793

PPX 90-Degree Adapter

PPX-3.5x16-2-STR | 93790

PPX Straight Toekick Connector and Grille

PPX-3.5x16-2-90 | 93789

PPX 90-Degree Toekick Connector and Grille

PPX TOEKICK REPLACEMENT GRILLE | 93799

Straight or 90-Degree Toekick Connector Required

DIMENSIONAL DRAWINGS

