

Accra



Colors



White
VTL ARWH




Light Gray
VTL ARLG




Medium Gray
VTL ARMG

Sizes



24" x 24" x 7.94mm
Rectified



12" x 24" x 7.94mm
Rectified

Field Tiles*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 24" Rectified	23.40" x 23.40"	7.94mm	Matte/Natural
24" x 24" Light Rectified	23.40" x 23.40"	7.94mm	Light or Semi-Polished
12" x 24" Rectified	11.63" x 23.38"	7.94mm	Matte/Natural
12" x 24" Light Rectified	11.63" x 23.38"	7.94mm	Light or Semi-Polished
* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.			

Mosaics & Coordinating Trims*

SIZE	ACTUAL	FINISH
3" x 24" Bullnose Rectified	2.78" x 23.40"	Matte/Natural
6" x 12" Cove Base	6.00" x 11.75"	Matte/Natural
1" x 6" Cove Base Outcorner	1.00" x 6.00"	Matte/Natural
Recommended Grout Joint: 1/8" - Rectified 3/16" - Non Rectified		

Product Characteristics

MATTE/NATURAL	
Breaking Strength (ASTM C648 or ISO 10545-4)	>275 lbs
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant
DCOF	≥0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	N/A
Mohs Hardness - EN101	8
Water Absorption (ASTM C373 or ISO 10545-3)	< 0.5
Certifications	N/A
Country of Origin	USA
Shade Variation Code	V2

Application**

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial		
** These recommendations are not defined by ANSI Standards			

Material

Color-Body Porcelain



Made in USA



Ready Ship



V2 Slight Variation



DCOF: ≥0.42



Scan QR Code for
Product Information and
Installation Images

Request samples.

www.vitlsurfaces.com
samples@vitlsurfaces.com

