

Type SOOW - 2-6 AWG

Type SOOW
EPDM Insulation - CPE Jacket
90°C - 600 Volt
2-6 AWG

Flexible and Portable Cord



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Fully annealed stranded bare copper

Category Insulation Description:

- Ethylene Propylene Diene Monomer (EPDM)

Category Jacket Description:

- Chlorinated Polyethylene (CPE)

Applications:

- Portable tools and equipment
- Portable appliances
- Small motors and associated machinery

Standards:

- MSHA Approved

PART NUMBER TABLE

Part#	Gauge	Conductors	Insulation Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
B10603	6	3	0.05	0.79	482
B10604	6	4	0.05	0.865	599
B10605	6	5	0.05	0.945	750
B10402	4	2	0.05	0.89	500
B10403	4	3	0.05	0.925	683
B10404	4	4	0.05	1.015	851
B10405	4	5	0.05	1.115	1039
B10203	2	3	0.055	1.085	1003
B10204	2	4	0.055	1.17	1248
B10205	2	5	0.055	1.39	1684

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC