

HUBBELL
Wiring Device-Kellems

**Locking Devices, Twist-Lock®,
Industrial, Flush Receptacle, 20A
250V AC, 2-Pole 3-Wire Grounding,
L6-20R, Screw Terminal, Black**

By Hubbell Wiring Device-Kellems
Catalog # [HBL2320](#)

Locking Devices, Twist-Lock®, Industrial, Single Flush
Receptacle, 20A 250V AC, 2-Pole 3-Wire Grounding, NEMA L6-
20R, Screw Terminal, Nylon face, Back and side wired, Black.



General

| | |
|------------------------------|--|
| Application | |
| Catalog Number | HBL2320 |
| Color | |
| EU RoHS Indicator | Yes |
| Environmental Conditions | Indoor Dry Unless Protected By Additional Means |
| Horsepower - Maximum | 2 |
| Item Type | Receptacles |
| Material | Nylon |
| Material - Mounting Hardware | Screw Mounting |
| Number Of Poles | 2-Pole |
| Operating Temperature | Maximum continuous 75°C and minimum -40°C without Impact |
| Performance | Electrical - Current Interrupting - Certified for current interrupting at full rated current |
| | Electrical - Dielectric Voltage - Withstands 2,000V minimum |
| | Environmental - Flammability - V2 or better per UL94/CSA 22.2 No.0.17 |
| | Environmental - Moisture Resistance - IP20 Suitability |
| | Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact) |
| | Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire only. |
| | Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 |
| Type | Single Flush Receptacle |
| | Single Flush Receptacle |
| UPC | 783585235585 |

Dimensions

| | |
|--------------|-----------------------------|
| Dimensions | 3.28 in x 1.70 in x 1.23 in |
| Display Size | Standard Sized Product |
| Height | 1.23 in |
| Length | 3.28 in |
| Weight | 0.25 lb |
| Width | 1.7 in |

Electrical Ratings

| | |
|----------------------------|---------------------------|
| Amperage Rating | 20 A |
| Connectivity | Back and Side Wired |
| Current / Amperage Rating | 20 A |
| Current Rating | 20 A |
| Dielectric Strength | Withstands 2,000V minimum |
| Phase | Single Phase |
| Voltage Rating | 250 VAC |
| Voltage Rating Description | 250 VAC |

Conductor Related

| | |
|-----------------|-------------------|
| Number Of Wires | 3-Wire |
| Wire Size | #16 AWG to #8 AWG |

Certifications And Compliance

| | |
|------------------------------------|------------------------------|
| Industry Standard(s) | Certified to CSA C22.2 No.42 |
| | Fed.Spec. W-C-596 |
| | Listed to UL 498 |
| Nema Rating | L6-20R |
| Standards - RoHS Compliance Status | CM |

Logistics

| | |
|-----------------|------|
| Carton Quantity | 10 |
| Pallet Quantity | 4050 |

Product Assets

[Catalogs - WDK Catalog Full 2024](#)
[Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
WDK_MX-HBL2320-SPEC-EN | REV 6/2024