

Eaton PLE225DD09NUX

Catalog Number: PLE225DD09NUX

Eaton Cooper Power series posi-break elbow, Northeast Utilities, 200 A, Std V:25 kV, Max phase-to-ground:15.2 kV, AC 1 min:40 kV, DC 15 min:78 kV, Impulse:125 kV, Max corona:19 kV, Test:No, 0.89 inch, 1.22 inch, 4/0 AWG, 250 AWG

General specifications



Product Name	Catalog Number
Eaton Cooper Power series posi-break elbow	PLE225DD09NUX
	UPC
	194006034401
Product Length/Depth	Product Height
10 in	3.75 in
Product Width	Product Weight
9 in	3.505 lb
Compliances	Certifications
Not Applicable	IEEE 386

defaultTaxonomyAttributeLabel

Special features

Northeast Utilities

Type

Posi-Break elbow

AC 1 minute voltage withstand

40 kV

Basic impulse level

125 kV

Cable insulation diameter - max

1.22 in

Cable insulation diameter - min

0.89 in

Solid or compact conductor size

250 AWG

Stranded or compressed conductor size

4/0 AWG

Current rating

200 A

DC 15 minute withstand

78 kV

Maximum rating phase-to-ground

15.2 kV

Corona voltage level - min

19 kV

Standard pack

Single

Standard voltage class

25 kV

Resources

Specifications and datasheets

[Eaton Specification Sheet - PLE225DD09NUX](#)

[Line installation and protective equipment specifiers guide](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia