

# Outpost



## Colors



White | VTL OPWH



Light Gray | VTL OPLG




Dark Gray | VTL OPDG




Black | VTL OPBK

## Sizes



24" x 24"



12" x 24"

# OUTPOST

## Field Tiles\*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 24"	24.00" x 24.00"	8.00mm	Matte/Natural
12" x 24"	12.00" x 24.00"	8.00mm	Matte/Natural

\* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.

## Mosaics & Coordinating Trims\*

SIZE	ACTUAL	FINISH
2" x 2" Mosaic	12.00" x 12.00"	Matte/Natural

Recommended Grout Joint: 1/8" - Rectified  
3/16" - Non Rectified

## Product Characteristics

	MATTE/NATURAL
Breaking Strength (ASTM C648 or ISO 10545-4)	≥ 300 lbf
Chemical Resistance (ASTM C650 or ISO 10545-13)	Resistant
DCOF	≥ 0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	N/A
Water Absorption (ASTM C373 or ISO 10545-3)	≤ 0.4%
Certifications	Carbon Neutral
Country of Origin	USA
Shade Variation Code	N/A

## Application\*\*

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

\*\* These recommendations are not defined by ANSI Standards

## Material

Porcelain



Made in USA



Ready Ship



DCOF: ≥0.42



Carbon Neutral



Scan QR Code for Product Information and Installation Images

## Request samples.

www.vitlsurfaces.com  
samples@vitlsurfaces.com



VITL  
COMMERCIAL SURFACES