Shades 2.0
Porcelain Stone®



## Shades 2.0

### Porcelain Stone®

# The evolution of design begins with Shades 2.0.

Continuing the tradition of the original Shades by Crossville, contemporary, elemental hues add warmth and depth to this perineal porcelain tile favorite. The subtle biophilic linear graphic is available in unpolished and semi-polished highlighting the soft striations of the finish. This directional visual was created to run in the same direction, or alternate to provide even greater visual texture. Still not enough? Shades 2.0 also offers a multi directional graphic in its new patterned accent tile designed to subtly stand out in a mix or work alone for maximum impact.

An expansive array of size offerings provide even more choices in shape and scale. With the addition of a 24"x48" tile, Shades 2.0 is suitable for even the largest of spaces. If you need something smaller in stature, a 2"x2" unpolished solid mosaic or 1"x3" semi-polished mosaic in cool or warm blends will fit your project's needs. Additional sizes include field tile in 6x24, 12x24, and 24x24, as well a new 12"x12" right triangle – all rectified - for an even bolder aesthetic. Complete your installation with a 4"x24" bullnose or 6"x12" cove base, both designed for beauty and functionality.

Shades 2.0 by Crossville is made in the U.S.A using Crossville's Ecocycle Tile Process™. It is Green Square Certified and Petal Certified by the International Living Future Institute, making it a beautiful responsible selection for your next design project.

Learn more at CrossvilleInc.com.






SHD52 ▶ Camel SPO 12 x 24 Artwork provided by Kristen Abbott



Floor: SHD51 > Foam 24 x 48 SPO

### Color Palette

#### **Available Colors**



SHD52 ▶ Camel UPS, SPO/PTN

SHD53 ▶ Russet UPS, SPO/PTN

SHD54 ▶ Midnight UPS, SPO/PTN


SHD51 ▶ Foam UPS, SPO/PTN

#### **Available Colors**


#### Mosaics



SHD1/.10103SMOS Warm Grays - SPO (SHD43, SHD45, SHD47)




SHD2/.10103SMOS Cool Grays - SPO (SHD44, SHD46, SHD48)



SHD3/.10103SMOS Whites - SPO (SHD41, SHD42)



SHD4/.10103SMOS - SPO (SHD51, SHD52, SHD53)



SHD46.0202UMOS Available in all colors UPS Finish SHD46 Haze UPS shown



**SHD/.10103SMOS** ▶ Warm Grays

### Specifications

#### Sizes Shown in SHD46 Haze SO)







12 x 12 Triangle



Mosaics Mosaics UPS

2 x 2 Solid 1 x 3 Blended (SHG04 Shown)

#### Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.



#### Sizes & Finishes

Field Tile	1	1	Available in all colo	rs
Nominal (in)	Actual (mm)		Grout Joint (mm)	Finish
6 x 24	147 x 597	9.5	3	UPS/SP0
	297 x 297	9.5	3	UPS
12 x 24	297 x 597	9.5	3	UPS/SPO/PTN
24 x 24	597 x 597	9.5	3	UPS/SPO
24 x 48	597 x 1197	10.5	3	UPS/SP0

Note: All field tile is rectified with a 3mm grout joint.

4	Mosaic				
	Nominal (in)	Actual (mm)	Sheet (mm)	Thickness (mm)	Finish
	1 x 3 Blended Mosaics	22 x 72	297 x 297	9.5	SPO
	2 x 2 Solid Mosaics	47 x 47	298 x 298	9.5	UPS

 $\dagger 1 \ge 3$  mosaics mesh mounted in 11-7/8  $\ge 11$ -7/8 sheets with 3mm grout joints.

### Coordinating Trim

Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
4 x 24 Single Bullnose	96 x 597	9.5	3	UPS/SPO
6 x 12 Cove Base	150 x 297	9.5	3	UPS





4 x 24 Single Bullnose

6 x 12 Cove Base

### **Product Performance**


Breaking Strength	500 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.30%	ASTM C373
Scratch Hardness	7	Mohs Scale

#### **Wet Dynamic Coefficient of Friction Range**

UPS	0.50 - 0.60	AcuTestsm
SP0	0.42 - 0.52	AcuTestsm
PTN	0.42 - 0.52	AcuTestsm

#### **Shade & Texture Index**

Shades by Crossville<sup>™</sup> has a shade variation of V2.



#### **V2 Slight Variation**

#### Recommended Use

Shades 2.0 is recommended for interior floors, walls, countertops, and exterior walls in both residential and commercial applications.

Shades 2.0 is not recommended for exterior horizontal surfaces or exterior paving. The semi-polished )

SPO) field tile is not recommended for wet areas where standing water may occur. If offset pattern is required for tiles 15 inches or longer, Crossville® recommended an offset of not greater than 33%.

See CrossvilleInc.com for detailed installation instructions.

#### Wet area use for Shades 2.0 1 x 3 SPO and 2 x 2 UPS Mosaics

Crossville® produces the Shades 2.0 1 x 3 mosaics with a semi-polished (SPO) finish and the 2 x 2 mosaics in the UPS finish. The AcuTest<sup>sm</sup> wet Dynamic COF of Shades 2.0 is ≥.42. Their small 1 x 3 and 2 x 2 size ensures frequent grout joints which provides traction and drainage. Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning. This information is provided so that customers may make a realistic and informed decision when comparing Shades 2.0 to other tile products in wet area environments, such as residential/commercial bathrooms. showers, and interior pool decks.

#### **Care and Maintenance**

Regular cleaning is the best way to keep Shades 2.0 tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.

#### **Our Warranty**

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1- 2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

#### HydroTect™

Our porcelain tiles are available with Hydrotect. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defense against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. For complete details check our website at CrossvilleInc.com.





#### Crossville® Sample Express

Sample fulfillment & Help Line Samples@CrossvilleInc.com 1800 221 9093

**Loose Samples for Architects & Designers** 

#### **Loose Tile Samples**

Sizes may vary depending on product series
Max. of 4 large field tile per order

### **Replacement Chips for PSS Rack** Max. of 5, 2 x 2 chips per color

**Standard Shipping** UPS Ground

#### CrossvilleInc.com

If you want a better idea of what Crossville tile would look like in a particular room setting, simply visit our website and click on Cross-Vision. This powerful software tool allows you to visualize different types of Crossville tile. In addition, you'll find comprehensive information about Crossville's entire portfolio of products. You can also learn about the latest styles and trends from industry experts, download detailed care and maintenance instructions for our various products, or browse electronic versions of Crossville's product brochures. So whether you need information about Crossville products or tile in general, please visit us at CrossvilleInc.com. Information listed here is subject to change.

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.


**Trade Organizations** 





















Shades 2.0

Crossville, Inc.

PO Box 1168 Crossville, TN 38557 Phone 931.484.2110 Fax 931.456.2956 F Mail Crosse@Crosse

E-Mail Crossc@CrossvilleInc.com
Web CrossvilleInc.com

