



## CRC LECTRA CLEAN EXTRA

Ref. : 10019

### 1. GENERAL DESCRIPTION

---

Non-flammable electrical parts cleaner.

CRC Lectra Clean is a heavy duty degreaser with strong cleaning action and fast evaporation. The chlorinated solvent blend is designed to quickly and effectively clean electrical/mechanical components, preventing failures and malfunctions caused by contaminants such as dust, dirt, grease and oil.

### 2. FEATURES

---

- Contains no ozone depleting chemicals: ODP = 0.
- Gives no contribution to global warming: GWP = 0.
- Promotes operating efficiency.
- Contributes to prolonged equipment life.
- Evaporates quickly and leaves no residue.
- Non-staining, non-corrosive and non-conductive.
- No flash point.
- May be harmful to some plastics, rubbers, adhesives and paints. (Test prior to use.)
- Aerosols are equipped with the 360° (upside-down) spray valve for added convenience.
- With non-flammable CO<sub>2</sub> propellant, giving an active product content of 97%.

### 3. APPLICATIONS

---

An effective heavy duty degreaser for:

- Air tools
- Bearings
- Compressors
- Chains & Wire ropes
- Dies & molds
- Mechanical brakes & clutches
- Motors
- Generators
- Tools
- Corroded machinery and parts.

### 4. DIRECTIONS

---

- Apply liberally by spraying or dipping and allow excess to run off. Use extension tube for hard-to-reach areas. In dipping bath applications, agitation enhances cleaning action. May also be applied by wiping or by brushing. To clean equipment interior, covers, plates, etc. should be removed prior to product application.



Manufactured by :  
CRC Industries Europe NV  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)





## CRC LECTRA CLEAN EXTRA

Ref. : 10019

- Allow to air dry or dry with absorbent cloth. After cleaning, use CRC 2-26 for lubrication and protection.
- May attack some plastics, rubbers, adhesives and paints. Do not use on polycarbonate or polystyrene. If in doubt, test on a small area before using or contact the manufacturer of the equipment.
- Do not use on sensitive electronic equipment such as tape desks, VCR's, computers, etc. Use one of CRC's contact cleaner products for this.
- Use only in well ventilated area.
- A safety data sheet (MSDS) according EU93/112 is available for all CRC products.

### 5. TYPICAL PRODUCT DATA (without propellant)

---

Appearance	: clear liquid
Odour	: chlorinated solvent
Distillation range	: 39 - 122°C
Freezing point	: < -20°C
Specific gravity (@ 20°C)	: 1,44
Vapour density (vs. air = 1)	: > 4
Kauri-Butanol value	: 150
Flash point (closed cup)	: none
Evaporation rate (vs. ether = 1)	: 4
Non-volatile content	: < 50 ppm
Surface tension (@ 20°C)	: 32 mN/m
Drying time (vertical) (*)	: < 0,5 hrs.

### 6. PACKAGING

---

bulk : 4 x 5 l  
20 l

(\*)Drying time will depend considerably on surface geometry and environmental conditions (temperature, % humidity, ventilation,...).

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com).

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10019 03 0503 00

Date : 25 september 2003



Manufactured by :  
CRC Industries Europe NV  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)

