

Specifications



Eaton LPC215

Eaton Cooper Power series loadbreak protective cap, Drain wire, 15 kV, Phase to ground: 8.3 kV, AC 1 min: 34.0 kV, DC 15 min: 53.0 kV, BIL: 95.0 kV, Min corona: 11.0 kV, 30 Kit bulk pack, 200 A

General specifications

PRODUCT NAME	Eaton Cooper Power series loadbreak protective cap
CATALOG NUMBER	LPC215
UPC	194006015844
PRODUCT LENGTH/DEPTH	2.8 in
PRODUCT HEIGHT	5.8 in
PRODUCT WIDTH	3.2 in
PRODUCT WEIGHT	1.39 lb
COMPLIANCES	Not Applicable
CERTIFICATIONS	IEEE Std 386

Product specifications

SPECIAL FEATURES	Drain wire
TYPE	Loadbreak protective cap
STANDARD PACK	30 Kit bulk pack
AC 1 MINUTE VOLTAGE WITHSTAND	34.0 kV
BASIC IMPULSE LEVEL	95.0 kV
DC 15 MINUTE WITHSTAND	53.0 kV
CURRENT RATING	200 A
RATING PHASE-TO-GROUND - MAX	8.3 kV
CORONA VOLTAGE LEVEL - MIN	11.0 kV
STANDARD VOLTAGE CLASS	15 kV

Resources

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - LPC215](#)

[Line installation and protective equipment specifiers guide](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

