



TECHNICAL INFORMATION



V3 Moderate
Variation




Ready Ship



DCOF: ≥ 0.42
(Penny Round Mosaic only)

COLORS

2 x 8 Glazed Porcelain Floor Tile



Crema MRZ IYCR



Ember MRZ IYEM



Olive MRZ IYOL



Indigo MRZ IYID



Ink MRZ IYIK


8" Glazed Porcelain Hexagon Floor Tile




Crema MRZ IYCR




Ember MRZ IYEM



Olive MRZ IYOL



Indigo MRZ IYID




Ink MRZ IYIK

MOSAICS


1" x 6" Glazed Ceramic Mosaic




Crema MRZ IYCR




Ember MRZ IYEM



Olive MRZ IYOL




Indigo MRZ IYID




Ink MRZ IYIK


Penny Round Glazed Ceramic Mosaic




Crema MRZ IYCR




Ember MRZ IYEM



Olive MRZ IYOL



Indigo MRZ IYID



Ink MRZ IYIK

Tiles, Mosaic and Trim

SIZE	ACTUAL	THICKNESS	FINISH
2" x 8"	2" x 7.9375	9.5mm	Satin
8" Hex	7.875" x 9.0625	7.94mm	Satin
1" x 6" Mosaic	9.75" x 11.5" (sheet size)	7.94mm	Satin
Penny Round Mosaic	11.375" x 13.375" (sheet size)	6.35mm	Matte

Application**

		Glazed Ceramic		Glazed Porcelain	
		WALL	FLOOR	WALL	FLOOR
Interior	Residential	•		•	•
Interior	Commercial	•		•	•
Interior	Heavy Commercial	•		•	
Exterior	Residential/Commercial				

** These recommendations are not defined by ANSI Standards

Performance Characteristics

	GLAZED CERAMIC	GLAZED PORCELAIN
Breaking Strength	>250 lbs	>275 lbs
Chemical Resistance	Resistant	Resistant
DCOF	Not Applicable	Not Applicable
Deep Scratch Resistance - Unglazed	Not Applicable	Not Applicable
Frost Resistance	Not Applicable	Not Applicable
Mohs Hardness - EN101	6-8	8
PEI Rating	Not Applicable	Not Applicable
Water Absorption	<3.0%	<0.5%
Certifications	Not Applicable	Not Applicable
Shade Variation Code	v3	v3