SONANCE

VISUAL EXPERIENCE EXTREME DATA SHEET

VXXT8RW SUBWOOFER

TECHNICAL SPECIFICATIONS

SKU 93736 - Each

Woofer 8" (203mm) polypropylene cone, high excursion Santoprene surround

Frequency Response 35Hz - 250kHz +/-3dB

Impedance 4 ohms nominal

Power Handling (RMS) 5 watts minimum; 200 watts maximum

Sensitivity (2.83V/1m) 90dB SPL

Environmental Compliance IP66 (Speakers), IP67 (Subwoofers), ASTM B117, ASTM G154/ASTM D4587, ASTM

D4329-13, ASTM D5112-98 (Horizontal), ASTM D3580-95 (Vertical), MIL-STD-810

Temperature Range -40°F to 194°F (-40°C to 90°C)

Round Micro Trim Grille (Dia) 11.54" (293.2mm)

Round Trimless Grille (Dia) 11.17" (283.8mm)

 Square Micro Trim Grille (WxH)
 11.53" x. 11.53" (293mm x 293mm)

 Square Trimless Grille (WxH)
 11.18" x. 11.18" (284mm x 284mm)


 Speaker Only (Dia x Depth)
 11.07" x 5.50" (232.8mm x 139.9mm)

 Mounting Depth (D)
 5.39" (137mm)


 Cut-Out Dims (Dia)
 10.125" (257mm)

Product Weight 11.35 lbs. (5.15kg) Each
Shipping Weight 14.99 lbs. (6.8kg) Each


DIMENSIONAL DRAWINGS







Side ViewMounting Depth



Front View Square Adaptor

VXXT8RW WOOFER ACCESSORIES

XPC-8RW-NT | 93747 8" Round XPC Trimless Grille | Each XPC-8RW-T | 93746 8" Round XPC Micro Trim Grille | Each XPC-8WSQ-NT | 93755 8" Square XPC Trimless Grille | Each XPC-8WSQ-T | 93754 8" Square XPC Micro Trim Grille | Each

ENVIRONMENTAL AND DURABILITY COMPLIANCE

This product is engineered and tested to meet rigorous environmental and durability standards, including:

IP66 (SPEAKERS): Dust-tight and protected against powerful water jets from any direction.

IP67 (SUBWOOFERS): Fully protected against dust ingress and capable of withstanding immersion in water up to 1 meter depth for 30 minutes.

ASTM B117: Salt spray (fog) testing to evaluate corrosion resistance.

ASTM G154/ASTM D4587: Accelerated weathering using fluorescent UV and condensation exposure.

ASTM D4329-13: UV exposure of plastics to simulate long-term sunlight degradation.

ASTM D5112-98 (HORIZONTAL), ASTM D3580-95 (VERTICAL): Vibration resistance under both horizontal and vertical orientations.

MIL-STD-810: U.S. military standard for environmental engineering considerations and laboratory tests, including temperature, humidity, vibration, and shock.

LIMITED FIVE (5) YEAR WARRANTY

Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for five (5) years. Sonance will at its option and expense either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. ©2025 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.

991 Calle Amanecer • San Clemente, CA 92673 USA • Phone: (949) 492-7777

08.25.2025