

COTTO REVIVAL™

GLAZED PORCELAIN FLOOR TILE AND GLAZED CERAMIC WALL & MOSAIC TILE

MARAZZI
DARE TO BE BOLD™

COTTO LOOK



COTTO REVIVAL™

A celebration of Spanish elegance, Cotto Revival™ pays homage to the historic artistry of handmade Talavera tile. A collection full of cotto inspiration in warm and cool tones are available in a glazed porcelain 8 x 8 and 8" hexagon as well as the linear 2 x 9 tile. Three 4 x 4 decorative wall tiles are offered in an array of patterns, colors, and geometric designs – perfectly crafted for statement walls and backsplashes. Add a finishing touch with the glossy, crackle finish 1 x 6 mosaic, available in rich jewel tones for a complete cultural experience.



COVER PHOTO: RUST, ALPACA AND MARBELLA
ABOVE PHOTO: LAGOS AND ASH

FINISHES: MATTE | GLOSSY

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



COTTO LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

4 x 4 DECO WALL TILE



CV58 Lagos*



CV59 Marbella*



CV60 Valencia*

*Available in 30 unique designs, which are pre-boxed in a random assortment. Individual designs are not sold separately

8" HEXAGON FLOOR TILE




CV50 Ash

CV51 Alpaca

CV52 Rust

CV53 Baltic


1 x 6 MOSAIC




CV54 Bay Crackle



CV55 Pollen Crackle



CV56 Clover Crackle



CV57 Spice Crackle

8 x 8 FLOOR TILE



CV50 Ash



CV51 Alpaca




CV52 Rust



CV53 Baltic


2 x 9 FLOOR TILE




CV50 Ash



CV51 Alpaca



CV52 Rust



CV53 Baltic



VISIT MARAZZIUSA.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE | GLOSSY

USAGE	MATERIAL	PRICING	SPECIAL FEATURES

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

COTTO LOOK

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	8 x 8 Floor Tile	7-15/16" x 7-15/16" (20.26 cm x 20.26 cm)	5/16"	11.00	25
	8" Hexagon Floor Tile	7-7/8" x 9-1/16" (19.95 cm x 23.04 cm)	5/16"	9.37	25
	2 x 9 Floor Tile	2-3/8" x 9-11/16" (6.00 cm x 24.60 cm)	5/16"	5.72	36
	4 x 4 Deco Wall Tile	3-7/8" x 3-7/8" (9.85 cm x 9.85 cm)	5/16"	5.67	54
	1 x 6 Mosaic (Mesh-mounted)	11-1/2" x 11-9/16" Sheet (29.20 cm x 29.50 cm Sheet)	5/16"	8.34	9

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	■*
Wet & Level – Interior Floor	≥ 0.42	■*
Shower Floors - Standard Center Drain (Residential or Light Commercial)	≥ 0.42	
Shower Floors - Linear Drain	≥ 0.60	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■*
Pool Linings	N/A	■**

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazziusa.com/DCOF.

APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Wall tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

Mosaic tile suitable for interior applications only.

* Floor tile only.

** 2 x 9 Floor tile and 4 x 4 Wall Deco tile only.

FEATURES

	POST-CONSUMER RECYCLED MATERIALS		PRE-CONSUMER RECYCLED MATERIALS
	MADE IN THE U.S.A.		REVEAL IMAGING®



All or select items within this series meet the requirements for these qualifications. For more information visit marazziusa.com.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 3/16" Wall & Mosaic: 1/8"	High Variation (Mosaic) Random Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Results	Wall Results	Mosaic Results
Water Absorption	C373	< 0.5%	< 20.0%	< 20.0%
Breaking Strength	C648	> 275 lbs	120 - 230 lbs	120 - 230 lbs
Scratch Hardness	MOHS	8.0	4.0 - 6.0	4.0 - 6.0
Chemical Resistance	C650	Resistant	Resistant	N/A*

For additional information on test results, visit us at: marazziusa.com/information/TestResults.

* See 1 x 6 Mosaics in NOTES.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazziusa.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

* For 1 x 6 mosaics.

Crackle tiles must be sealed with a penetrating sealer prior to grouting to prevent the grout from staining the mosaic. For best results, use a grout color to match the tile.

Wall installation only, where tile will not come into contact with staining agents including food.

Not recommended for wet areas, countertops or floors.

Periodic resealing of crackle tile is required.