

OVAL EYEBOLT

- Commonly used as an attachment point to secure thimbles, clevises, links and deadend insulators
- Forged, one-piece design
- Supplied assembled with square nut
- Eye I.D. - 1 1/2" width x 2" length
- Constructed of high quality steel, hot-dip galvanized
- U.S. made versions available

5/8" Oval Eyebolt - Minimum Tensile Strength 13,550 Lbs.

Part Number	Bolt Length	Thread Length	Carton Qty	Carton Weight
J9406	6"	4"	50	57 Lbs.
J9408	8"	4"	25	32 Lbs.
J9409	9"	4"	25	35 Lbs.
J9410	10"	6"	25	35 Lbs.
J9412	12"	6"	25	39 Lbs.
J9414	14"	6"	25	43 Lbs.
J9416	16"	6"	25	48 Lbs.
J9418	18"	6"	25	50 Lbs.
J9420	20"	6"	25	53 Lbs.

3/4" Oval Eyebolt - Minimum Tensile Strength 20,050 Lbs.

Part Number	Bolt Length	Thread Length	Carton Qty	Carton Weight
J9508	8"	4"	25	43 Lbs.
J9510	10"	6"	25	50 Lbs.
J9512	12"	6"	25	56 Lbs.
J9514	14"	6"	20	47 Lbs.
J9516	16"	6"	20	52 Lbs.
J9518	18"	6"	20	57 Lbs.



DOUBLE ARMING OVAL EYEBOLT

- Commonly used as a combination double arming bolt as well as an eyebolt
- Forged, one-piece design
- Eye I.D. - 1 1/2" width x 2" length
- Fully threaded entire bolt length except 2" under the eye
- Supplied assembled with 3 square nuts
- Constructed of high quality steel, hot-dip galvanized

5/8" Double Arming Eyebolt - Minimum Tensile Strength 13,550 Lbs.

Part Number	Bolt Length	Thread Length	Carton Qty	Carton Weight
J9614	14"	12"	25	47 Lbs.
J9616	16"	14"	25	57 Lbs.
J9618	18"	16"	25	60 Lbs.
J9620	20"	18"	15	38 Lbs.
J9622	22"	20"	15	41 Lbs.
J9624	24"	22"	15	44 Lbs.
J9626	26"	24"	15	47 Lbs.

3/4" Double Arming Eyebolt - Minimum Tensile Strength 20,050 Lbs.

Part Number	Bolt Length	Thread Length	Carton Qty	Carton Weight
J9636	16"	14"	15	46 Lbs.
J9638	18"	16"	15	49 Lbs.
J9640	20"	18"	15	52 Lbs.
J9642	22"	20"	10	35 Lbs.
J9644	24"	22"	10	38 Lbs.
J9646	26"	24"	10	41 Lbs.

