



Order No. **RLG25**  
Model No. **X-RLG25**

Notes:

## Section 10309 - Manufactured Electric Fireplaces

### PART 1 GENERAL

#### 1.1 SECTION INCLUDES

- A. Manufactured electric fireplaces.
- B. Accessories

#### 1.2 RELATED SECTIONS

- A. Section 06100 - Rough Carpentry: Wood framed rough opening and enclosure.

#### 1.3 REFERENCES

- A. cULus - 1278
- B. CSA - C22.2 no 46-13

#### 1.4 SUBMITTALS

- A. Submit under provisions of Section 01300.
- B. Product Data: Manufacturer's data sheets on each product to be used, including:
  - 1. Preparation instructions and recommendations.
  - 2. Storage and handling requirements and recommendations.
  - 3. Installation methods.
- C. Manufacturer's Certificates: Certify products meet or exceed specified requirements.
- D. Manufacturer's warranty.

#### 1.5 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.
- B. Protect materials from exposure to moisture. Do not deliver until after wet work is complete and dry.

#### 1.6 WARRANTY

- A. Provide the manufacturer's 2-year limited warranty on electrical components.

### PART 2 PRODUCTS

#### 2.1 ACCEPTABLE MANUFACTURERS

- A. Pre-fabricated Electric Fireplace:
  - 1. Base: Dimplex Electric Fireplace  
Glen Dimplex Americas  
1367 Industrial Road  
Cambridge ON N3H 4W3  
1-888-346-7539  
www.dimplex.com
  - 2. Substitutions not permitted
  - 3. Requests for substitutions will be considered in accordance with provisions of Section 01600.



Order No. **RLG25**  
Model No. **X-RLG25**

Notes:

## Section 10309 - Manufactured Electric Fireplaces

### 2.2 ELECTRIC FIREPLACES

#### A. General:

1. Provide all components and accessories required for a complete, functional unit.
2. UL or CSA listed

#### B. Pre-fabricated Electric Fireplace:

1. Base Product:
  - a) Dimplex Plug-in Electric Log Set
  - b) Model Number: RLG25
2. Description: Revillusion 25" Plug-in Electric Log Set
3. Dimensions:
  - a) Width: 25-5/8" / 65.0 cm
  - b) Height: 19" / 48.2 cm
  - c) Depth: 13" / 32.9 cm
4. Framing Dimensions:
  - a) Width: 26" / 66.0 cm
  - b) Height: 22" / 55.9 cm
  - c) Depth: 15" / 38.1 cm
5. Electrical:
  - a) Volts: 120 V
  - b) Watts: 1500 W
  - c) BTU: 5188
  - d) Amps: 12.5
6. Venting: Non-venting
7. Operation: Flame only, flame and heat
8. Heating: Louver-less, fan-forced circulation
9. Liner: Steel
10. Standard features:
  - a) Patented flame technology create brighter and more random flames
  - b) Partially frosted acrylic panel highlights flame without any reflections
  - c) Customizable firebox hues, mood lighting to adjust firebox light level
  - d) Powerful fan-forced heating capabilities
  - e) Easy installation – plug into any standard household outlet
11. Control options:
  - a) Multi-function remote control
  - c) Built-in controls



Order No.	<b>RLG25</b>
Model No.	<b>X-RLG25</b>

Notes:

## Section 10309 - Manufactured Electric Fireplaces

### PART 3 EXECUTION

#### 3.1 INSPECTION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.
- C. Verify proper power supply and fuel source are available.

#### 3.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

#### 3.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions and requirements of authorities having jurisdiction.
- B. Use manufacturer's guidelines for minimum clearances to combustibles, walls, and finishes.
- C. Anchor all components firmly in position for long life under hard use.
- D. Upon completion of installation, visually inspect all exposed surfaces. Touch up scratches and abrasions with touch up paint recommended by the manufacturer; make imperfections invisible to the unaided eye from a distance of 5 feet (1.5 m).
- E. To use the mobile app, install where a WiFi connection is available.

#### 3.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

**END OF SECTION**



Order No. **RLG25**  
Model No. **X-RLG25**

Notes:

## Framing / Placement:

The Revillusion log set does not require venting. For optimal viewing, it is recommended to install the unit in an opening with the following minimum dimensions:

- A.** 26" (66.0 cm) wide,
- B.** 22" (55.9 cm) high
- C.** 15" (38.1 cm) deep.

Make sure there is clearance for air circulation beneath the unit.

If installing in an existing fireplace opening, seal all drafts and vents with a non-fibrous insulation material to prevent any chimney debris from falling onto the unit. Do not install into an existing fireplace opening that is prone to dampness.

