## Splice Tray, Heat-shrink Fusion Splices Long, 0.2-in, 24 F



### Part Number: M67-112

Corning splice trays use proven designs and fiber organization technology to provide optimum physical protection for fusion and mechanical splicing methods. The trays are engineered for use with indoor or outdoor splice hardware with both loose tube and tight-buffered optical cable designs. The metal-tray series consists of a rugged aluminum base and cover with crimpable metal tabs for buffer tube strain-relief. Additional strain-relief points are available for securing buffer tubes or pigtails to the trays using cable ties. The black powder coating allows easy fiber identification and additional protection. Designed for use with Corning interconnection hardware and splice closures, these splice trays are an integral part of a complete splicing system. Many of our fiber optic hardware products are highly configurable. If you don't see what you are looking for here, please review the ordering matrix contained in the family spec sheet found on the right, or contact Customer Care at 1-800-743-2675.

#### **Features and Benefits**

Metal trays powder coated


Ruggedness and durability

Fiber loop retention

Controls the bend radius

Positive holding action

Maximum splice protection



# Splice Tray, Heat-shrink Fusion Splices Long, 0.2-in, 24 F



#### **Specifications**

General Specifications	
Product Type	Splice Trays
Technology	Fusion Splice
Application	Carrier Networks, CATV Environments, Central Office, Enterprise Networks

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Design	
Splice Tray Type	Standard with organizers for heat-shrink fusion splice protectors
Splice Tray Category	2S Long
Splice Protectors Type	Heat Shrink
Splice Tray Capacity Single Fiber	24 N/A
Housing Type	Splice Trays

Ordering Information	
Product Number	M67-112
EAN Code	4056418192956
Package Contents	Installation Guide; splice tray base with splice holder; splice tray cover
Units per Delivery	1/1

## Splice Tray, Heat-shrink Fusion Splices Long, 0.2-in, 24 F





Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States 800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • <a href="https://www.corning.com/opcomm">www.corning.com/opcomm</a>

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2023 Corning Optical Communications. All rights reserved.