Thin Wall Conduit Fittings (for EMT Conduit)

Compression Type Fittings – Steel

COMPRESSION TYPE FITTINGS – STEEL

Applications:

Thin wall conduit fittings are used:

- To join EMT to a box or enclosure
- To couple two ends of EMT conduit

Features:

- Compression type
- Threadless
- Male hub threads – NPSM
- Steel locknuts
- Heavy steel walls
- Standard material: steel
- Standard finish: zinc plated

Concrete Tight Straight Connectors – Insulated

UL File No. E-22132



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
1650	½″	50	11
1651	¾″	25	16
1652	1″	25	25
1653	1¼″	10	43
1654	1½″	10	54
1655	2″	5	76
1656	2½″	2	190
1657	3″	1	300
1658	3½ ″	1	330
1659	4″	1	360

Straight Connectors – Non-insulated

UL File No. E-22132



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
650S	½″	50	9
651S	¾″	25	16
652	1″	25	25
653	1¼″	10	43
654	1½″	10	54
655	2″	5	76
656	2½″	2	190
657	3″	1	300
658	3½ ″	1	280
659	4″	1	360

Couplings

UL File No. E-22132



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
660S	½″	50	12
661S	¾″	25	18
662	1″	25	27
663	1¼″	10	46
664	1½″	10	63
665	2″	5	92
666	2½″	2	250
667	3″	1	410
668	3½ ″	1	390
669	4″	1	485

Available in 7 Colors

Crouse-Hinds series painted EMT fittings consists of set screw, compression, insulated and non-insulated EMT fittings. Although red is the most commonly used, other colors offered include white, blue, green, yellow, black, and orange. These can also be used in architectural design, to better match look and feel to suit architectural specification and preference.



Red White Blue Yellow Orange Green Black

Part Number Example:

650SGreen

Non-insulated Straight Connector	
½″	**650S**
¾″	**651S**
1″	**652**
1¼″	**653**
1½″	**654**
2″	**655**
2½″	**656**
3″	**657**
3½ ″	**658**
4″	**659**

Color
Red
White
Blue
Yellow
Orange
Green
Black

To order, simply add the name of the color needed after the catalog number.