

FLAT TIRE FIX

Technical Data Sheet

Creation Date 24/06/2020

Version I

CRC Flat Tire FIX seals and inflates a flat tire with a non-flammable gas in a few seconds.

Where to use?

Clean and easy to use on all types of tubeless tires on cars, campers and motorcycles. A fast, temporary relief in emergency situations when changing a tire is inconvenient.

How does it work?

CRC Flat Tire Fix gives a fast and easy fix by inflating the tire in a few seconds. It will form a stable, durable film inside the tire. Inflates the tire from flat (no pressure) to driving pressure.

What to expect?

CRC Flat Tire Fix seals small leaks in the tire and inflates in a few seconds enabling to drive to a service facility.

Be prepared

- Read the instructions carefully before start.
- Always make sure to have a good ventilation
- Wear protective safety goggles and nitril gloves.
- Dispose empty cans according to your local legislation

Help for a good application

- If possible, remove the cause of the puncture.
- Shake well before use. In cold weather, warm the can with hands or in front of the car heating system. Never exceed 50°C.
- Screw nozzle firmly onto tire valve.
- Remove protective cap from aerosol. Hold can upright. Press button to fill tyre. Continue until tire is inflated.
- Disconnect.
- Immediately drive 5 to 10 km, at moderate speed, to allow the product to act.
- Have your tire examined by a professional.
- As soon as possible deflate tire totally and refill tire with compressed air to the prescribed pressure.
- Punctures caused by objects over 5 mm diameter, ripped sidewalls etc. should be repaired the conventional way.

Technical data (Aerosol)

Appearance: Milky Liquid

Volume: 500 ML

Odour: Neutral

Related products:

CRC Wipes



All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

