



Optima® Sensor Faucet
Optima® Sensor Faucet

ETF-600 SMT-PLG-TEE-CP-0.35GPM-MLM-FCT

Product description

Trim Plate: None, Plug Adapter Power Supply, Back-Check Tee, Polished Chrome Finish, 0.35 gpm, Multi-Laminar Spray, Infrared Sensor, Optima® Hardwired-Powered Deck-Mounted Low Integrated Base Body Faucet

Optima® Hardwired-Powered Deck-Mounted Low Integrated Base Body Faucet.

Compliances & Certifications



(ADA Compliant, ASME A112.18.1 Compliant, BREEAM Materials Credit, BREEAM Water Credit, CalGreen Compliant, CEC Compliant, cULus Certified, EPD, Green Globes Credit, Green Globes Water, HPD, LEED Credit, LEED HPD, LEED Water, NSF-61/CAN-61, NYC604.4, Proposition 65, Satisfies LEED Credits, TAS, WELL Building Standard)

Code 3365773BT

Finish

- Polished Chrome (CP)

Connectivity

- Bluetooth with Sloan Connect App

Downloads

- [Optima Smart Faucet Below Deck Installation Instructions.pdf](#)
- [Trim Plate Guide.pdf](#)
- [Faucet Spray Heads Maintenance Guide.pdf](#)
- [ETF-600:EBF-650 Below Deck Repair and Maintenance Guide.pdf](#)
- [Additional Downloads](#)
www.sloan.com/products/faucets/optima/ETF-600"),>

Videos

- Sloan Connect App®
Sloan Connect App®
<https://vimeo.com/472228825>"),>

- PVD Special Finishes
PVD Special Finishes
Revised 01/07/2026 | Page 1 of 3
Sloan 10500 Seymour Ave, Franklin Park, IL 60068-2839 [sloan.com](http://www.sloan.com)
<https://vimeo.com/345935647>"),>
- Sloan Optima Below Deck Faucet

Details

- Flow Rate: 0.35 gpm (1.3 Lpm) (0.35GPM)
- Spray Type: Multi-Laminar (MLM)
- Sensor Type: Infrared
- Mounting Type: 4" Centerset
- Mounting Size: 4" Centerset, (3-hole) 1-1/4" to 1-1/2"
- Trim Plate: None
- Power Supply: Plug Adapter (PLG)
- Temperature Mixer: Back-Check Tee (TEE)
- Finish: Polished Chrome (CP)
- Factory Default Timeout: 30s
- Factory Default GPC: 0.175 gpc
- IOT:

Features

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Hand Washing Faucet with the following features:

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Hand Washing Faucet with the following features:

- Commercial Grade Faucet
- Commercial Grade Faucet
- ADA Compliant
- ADA Compliant
- Cast Brass Spout
- Cast Brass Spout
- Quick Connect Fittings
- Quick Connect Fittings
- Integrated Water Shut-off
- Integrated Water Shut-off
- Wireless Settings Adjustment
- Wireless Settings Adjustment
- On-demand or Metered activation
- On-demand or Metered activation
- Hygienic Line Flush
- Hygienic Line Flush
- Water Usage and Battery Strength Reporting
- Water Usage and Battery Strength Reporting
- Self-adapting Sensor
- Self-adapting Sensor

Recommended specifications

Faucet shall include cast brass body, quick-connect fittings, twist-off/shut-off solenoid assembly, removable battery cartridge, flexible power supply and allow adjustment of settings wirelessly via Apple or Android smartphones.

Electrical specifications

- Battery Life: 3 years 8,000 cycles/month
- Optional power harvesting significantly extends service life
- Sensor Range: 4" -5" (102-127 mm)
- Timeout Adjustment Setting: 30 Seconds

Power Supply Options

- 6VDC Ganged Adapter Kit (up to 6 units)(sold separately)/0362035
- 6VDC Plug Adapter (included with PLG models)/0362006
- 24VAC Box Transformer (included with BOX models)/0345370PK

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Looking for other variations of the ETF-600 SMT product? [View the general spec sheet with all options.](#)
www.sloan.com/products/faucets/optima/ETF-600,">

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet

Rough-in and line drawing ETF-600 SMT-PLG-TEE-CP-0.35GPM-MLM-FCT

