



GE
Lighting

SAFETY & PERFORMANCE

- cUL_Listed
- FCC_CS_NCons
- NR_Can
- UL_Cls_P
- UL_Listed
- UL_Type1_Out
- UL_Type_CC
- UL_Type_HL
- NEMA_Pre

72262 - GE LFL UltraMax™ Professional Series Electronic High Efficiency Multivolt Instant Start Ballast

GE232MAXP-L/ULTRA (replaces GE232MAX-L/ULTRA)

- Energy saving high efficiency instant start electronic ballast (> 90%)
- Multi-Voltage Technology handles voltage from 120 to 277V
- UL Type CC Rating provides protection against arcing in electrical devices.
- Anti-Striation Control for better light quality, with no striations.
- Cold temperature -20F Minimum Starting Temperature

Product Photo



CAUTIONS & WARNINGS

Warning

Risk of Electric Shock

Properly ground ballast and fixture.

Turn power off before servicing--see instructions.

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% ($\geq$)	Crest Factor ($\leq$)	THD% ($\leq$)	Min. Starting Temp (F/ C)
F17T8	1	120	17	0.14	0.79	5	0.99	1.5	11	-22
F17T8	1	277	17	0.08	0.79	5	0.8	1.5	36	-22
F17T8	2	120	27	0.23	0.79	3	0.99	1.5	8	-22
F17T8	2	277	27	0.1	0.79	3	0.95	1.5	12	-22
F25T12	1	120	24	0.2	0.8	3	0.99	1.5	9	0
F25T12	1	277	24	0.09	0.8	3	0.94	1.5	13	0
F25T12	2	120	41	0.35	0.8	2	0.99	1.5	6	0
F25T12	2	277	41	0.15	0.8	2	0.98	1.5	9	0
F25T8	1	120	23	0.19	0.8	3	0.99	1.5	9	-22
F25T8	1	277	23	0.09	0.8	3	0.93	1.5	13	-22
F25T8	2	120	39	0.33	0.8	2	0.99	1.5	6	-22
F25T8	2	277	39	0.14	0.8	2	0.97	1.5	10	-22
F28T8	1	277	25	0.1	0.77	3	0.94	1.5	13	60
F28T8	1	120	25	0.21	0.77	3	0.99	1.5	8	60
F28T8	2	120	43	0.36	0.77	2	0.99	1.5	6	60
F28T8	2	277	42	0.16	0.77	2	0.98	1.5	9	60
F32T8/WM	1	120	27	0.23	0.78	3	0.99	1.5	8	60
F32T8/WM	1	277	27	0.1	0.78	3	0.95	1.5	12	60
F32T8/WM	2	120	47	0.39	0.78	2	0.99	1.5	5	60

F32T8/WM	2	277	46	0.17	0.78	2	0.98	1.5	9	60
F32T8	1	120	28	0.23	0.77	3	0.99	1.5	8	-22
F32T8	1	277	28	0.11	0.77	3	0.95	1.5	12	-22
F32T8	2	120	48	0.42	0.78	2	0.99	1.5	5	-22
F32T8	2	277	48	0.19	0.78	2	0.98	1.5	8	-22
FE15T8	1	120	14	0.12	0.78	6	0.99	1.5	12	0
FE15T8	1	277	15	0.07	0.78	5	0.73	1.5	40	0
FE15T8	2	120	21	0.18	0.78	4	0.99	1.5	9	0
FE15T8	2	277	22	0.09	0.78	4	0.93	1.5	13	0
F32T8/25W	1	277	22	0.0	0.77	4	0.97	1.5	10	60
F32T8/25W	2	277	38	0.0	0.77	2	0.98	1.5	10	60
F25T8/WM	1	277	21	0.09	0.8	3	0.9	1.5	13	-22
F17T8/WM	2	120	24	0.21	0.81	3	1.0	0.5	8	-22
F17T8/WM	2	277	24	0.1	0.81	3	0.94	1.5	12	-22
F17T8/WM	1	120	16	0.14	0.81	5	0.99	1.5	11	-22
F17T8/WM	1	277	16	0.08	0.81	5	0.79	1.5	36	-22
F25T8/WM	2	277	34	0.13	0.81	2	0.97	1.5	10	-22
F29T8	2	120	46	0.39	0.78		1.0			
F29T8	1	120	28	0.23	0.78		1.0			
F29T8	2	277	46	0.17	0.78		0.98			
F29T8	1	277	28	0.11	0.78		0.95			
F31T8	2	120	49	0.41	0.77		1.0			
F31T8	1	120	28	0.24	0.77		1.0			
F31T8	1	277	28	0.11	0.77		0.95			
F31T8	2	277	48	0.18	0.77		0.98			
F26T8	1	120	26	0.22	0.77		1.0			
F26T8	2	120	42	0.36	0.76		1.0			
F26T8	2	277	42	0.16	0.76		0.98			
F26T8	1	277	26	0.1	0.77		0.95			