

# PC 745



## T-REX® PC 745 SUPER-TOUGH, PREMIUM, CO-EXTRUDED CLOTH TAPE

### TYPICAL APPLICATIONS

- For heavy duty repairs that demand a ferociously strong hold
- Use to bundle, support or haul heavy loads or for seaming projects
- For seaming and sealing bottom board materials in pre-manufactured housing and RV assembly, set-up and maintenance
- Can also be used to protect surfaces in metal-peening operations
- For use on wet, rough or dirty surfaces

### PRODUCT FEATURES

- Double-thick adhesive built for heavy-duty repairs that demand a ferociously strong hold
- Duct tape made with Polybonded CO-EX Technology® that prevents delamination and heavy-duty knit cloth to bundle, support or haul heavy loads or for seaming and sealing projects
- Adheres well to brick, concrete, shingles, painted and non-painted wood, vinyl siding and more
- Tape can be torn by hand and is easy to unwind for hassle-free application

### CONSTRUCTION

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber adhesive

### STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

### STANDARD LENGTHS

10 yd, 30 yd

9.14 m, 27 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

### STANDARD CORE SIZE

3 in

### APPLICABLE STANDARDS

Tested in accordance with UL 723

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLORS



### PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	150 oz/in width	16.42 N/10 mm
Elongation	21%	21%
Service Temperature Range	32 F to 200 F	0 C to 93 C
Tensile	47 lbs/in width	82.3 N/10 mm
Thickness - Nominal	16.0 mils	0.41 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

