



Overview

Model Name	APC Easy UPS On-Line SRV RM 3000VA 120V, with Rail Kit
Includes	CD with software , USB cable , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Anguilla , Antigua And Barbuda , Argentina , Aruba , Bahamas , Barbados , Belize , Bermuda , Bolivia , Brazil , Cayman Islands , Chile , Colombia , Costa Rica , Cuba , Dominica , Dominican Republic , Ecuador , El Salvador , Falkland Islands (Malvinas) , Grenada , Guatemala , Guyana , Haiti , Honduras , Jamaica , Mexico , Netherlands Antilles , Nicaragua , Panama , Paraguay , Peru , Puerto Rico , SAINT KITTS AND NEVIS , SAINT LUCIA , SAINT VINCENT AND THE GRENADINES , Trinidad And Tobago , Uruguay , Venezuela , VIRGIN ISLANDS (UNITED STATES)

Output

Output Power Capacity	2400 Watts / 3000 VA
Max Configurable Power (Watts)	2400 Watts / 3000 VA
Nominal Output Voltage	120V
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	110, 115V
Crest Factor	3 : 1
Waveform Type	Sine wave
Output Connections	(1) NEMA L5-30R (Battery Backup) , (6) NEMA 5-20R (Battery Backup)

Input

Nominal Input Voltage	120V
Input Frequency	40 - 70 Hz
Input Connections	NEMA L5-30P
Other Input Voltages	110 , 115

Communications & Management

Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	600 Joules
---------------------	------------

Physical

Maximum Height	86.0 mm
Maximum Width	437.0 mm
Maximum Depth	632.0 mm
Net Weight	27.6 kg
Shipping Weight	29.0 kg
Shipping Height	229.0 mm
Shipping Width	569.0 mm
Shipping Depth	795.0 mm

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-3000 meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-14763.6 meters
Audible noise at 1 meter from surface of unit	0.000 dB

Conformance

Approvals	CE , IEC 62040-1-1 , IEC 62040-1-2
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains SVHCs
REACH SVHC	Lead, CAS#7439-92-1 30% , SVHC-191