

DOUBLE-SIDED UPVC TAPE



UV RESISTANCE

HIGH ADHESION

DESCRIPTION

2.0 mil UPVC film coated on both sides with pressure-sensitive acrylic adhesive. Provides exceptional shear strength, good adhesion and high initial tack allowing immediate/permanent bond to a variety of surfaces including surfaces such as metal, wood, glass, cement and plastics. Features an easy release 3 mil glassine paper liner (gold).

APPLICATIONS

- Fastening of nameplates, trophy, luggage tags, wooden trim, signs, etc.
- Fastening of decorative trims (e.g. PVC profile, stainless steel and plastic parts) and any application that requires the joining of two surfaces.

TECHNICAL DATA

Color..... White
 Backing 2 mil (50.8µ) UPVC
 Adhesive..... Solvent Acrylic
 Adhesion to steel..... 88 oz/in (2.5 kg/25mm)
 Elongation..... 150% (MD) / 120% (CD) at break
 Thickness w/o Liner 8.3 mil
 Shear Adhesion to Steel..... >72 hours (1"x1"x1 kg at 77°F / 25°C)
 Service Temperature (Short Term) -22°F to +194°F (-30°C to +90°C)

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.