



TECHNICAL INFORMATION



V2 Slight
Variation



Import



Recommend
offset pattern
≤33%



DCOF:
≥ 0.42



Made in
Italy

COLORS



Chalk CAE PMCH




Ecrú CAE P MEC



Concrete CAE PMCN




Clay CAE PMCL



Lead CAE PMLD



Powder CAE PMPW



Avio CAE PMAV



Sienna CAE PMSN

MOSAIC AND DECOS

COMP Q



Chalk
CAE PMCH



Ecrú
CAE P MEC



Concrete
CAE PMCN



Clay
CAE PMCL



Lead
CAE PMLD



Powder
CAE PMPW



Avio
CAE PMAV




Sienna
CAE PMSN

COMP R



Chalk
CAE PMCH



Ecrú
CAE P MEC



Concrete
CAE PMCN




Clay
CAE PMCL



Lead
CAE PMLD



Powder
CAE PMPW




Avio
CAE PMAV



Sienna
CAE PMSN

COMP S



Chalk
CAE PMCH




Ecrú
CAE P MEC



Concrete
CAE PMCN




Clay
CAE PMCL



Lead
CAE PMLD



Powder
CAE PMPW



Avio
CAE PMAV



Sienna
CAE PMSN



Golden Willow CAE PMGW



Impression CAE PMIM



Rammed CAE PMRM

Tiles, Mosaic and Trim*

SIZE	ACTUAL	THICKNESS	FINISH
48" x 110" Rectified	47.25" x 109.4375"	6mm	Matte
48" x 110" Deco Rectified	47.25" x 109.4375"	6mm	Soft
48" x 48" Rectified	47.25" x 47.25"	9mm	Soft
24" x 48" Rectified	23.625" x 23.625"	9mm	Matte & Soft
32" x 32" Rectified	31.5" x 31.5"	9mm	Matte
32" x 32" Rectified	31.5" x 31.5"	20mm	Textured
24" x 24" Rectified	23.625" x 23.625"	9mm	Matte
24" x 24" Rectified	23.625" x 23.625"	20mm	Textured
12" x 24" Rectified	11.81" x 23.625"	9mm	Matte
6" x 6" Comp Q Mosaic	11.4375" x 11.4375" (sheet size)	9mm	Matte & Soft
3" x 3" Comp R Mosaic	11.4375" x 11.4375" (sheet size)	9mm	Matte & Soft
2" x 6" Comp S Mosaic	11.4375" x 11.4375" (sheet size)	9mm	Soft
3" x 24" Bullnose	2.8125" x 23.625"		Matte
13" x 48" Step Tread	13" x 47.25"		Matte
13" x 13" Step Tread Corner	13" x 13"		Matte

* Not all sizes are available in all colors and finishes



Performance Characteristics

	MATTE & SOFT	TEXTURED
Breaking Strength	≥1300 N	≥10000 N
Chemical Resistance	Resistant	Resistant
DCOF	≥0.42	≥0.55
Deep Scratch Resistance - Unglazed	Not Applicable	Not Applicable
Frost Resistance	Resistant	Resistant
Mohs Hardness - EN101	Not Applicable	Not Applicable
PEI Rating	Not Applicable	Not Applicable
Water Absorption	≤0.1%	≤0.1%
Certifications	Not Applicable	Not Applicable
Shade Variation Code	v2	v2



Application**

		Matte		Soft		Textured	
		WALL	FLOOR	WALL	FLOOR	WALL	FLOOR
Interior	Residential	•	•	•	•	•	•
Interior	Commercial	•	•	•	•	•	•
Interior	Heavy Commercial	•		•		•	
Exterior	Residential/Commercial	•	•	•		•	•

** These recommendations are not defined by ANSI Standards