



TECHNICAL INFORMATION



V3 Moderate Variation



Ready Ship



Recommend offset pattern  $\leq 33\%$



PEI Rating 3



Frost Resistant



Water Absorption:  $< 0.5\%$




COLORS



Gray  
VTC SBGY



White  
VTC SBWH



Green VTC SBGR  
(ONLY Available in 24" x 48" Polished)

Performance Characteristics

Breaking Strength	$\geq 425$ lbs
Chemical Resistance	Class E
DCOF	N/A
Deep Scratch Resistance - Unglazed	N/A
Frost Resistance	Resistant
Mohs Hardness - EN101	4,5
Water Absorption	$< 0.5\%$
Certifications	N/A
Country of Origin	N/A
Shade Variation Code	V3

Tiles, Mosaic and Trim\*

SIZE	ACTUAL	THICKNESS	FINISH
24" x 48" Rectified	23.56" x 47.31"	9 mm	Polished
12" x 24"	11.75" x 23.56"	9mm	Polished
12" x 24" Rectified	11.75" x 23.56"	9mm	Matte/Natural
3" x 3" Hex Mosaic Rectified	10.25" x 11.75"	9mm	Polished
2" x 2" Mosaic Rectified	11.75" x 11.75"	9mm	Matte/Natural
3" x 24" Bullnose	2.75" x 23.56"		Polished

\* Not all sizes are available in all colors and finishes.

Application\*\*

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	

\*\* These recommendations are not defined by ANSI Standards



Please see [virginiatile.com](http://virginiatile.com) for details