

GLOW FISH RODS

NON-CONDUCTIVE FIBERGLASS



NON-CONDUCTIVE FIBERGLASS RODS FOR WIRING

With our proprietary luminescent resin, Jameson is the original manufacturer of fiberglass glow rods.

These non-conductive rods are perfect for attics, drop ceilings, floors, walls, and crawl spaces. Their high strength and flexibility will handle turns easily without breaking.

Designed for maximum versatility, threaded ferrules make it possible to customize rod length to any job and a variety of accessories make it easier to handle any wiring situation.

1/4" DIAMETER GLOW RODS

Minimum Bend Radius: 6"

Most Rigid Glow Rod; Used For Long Spans

Tensile/Pull Strength: 750 lbs

Part Number	Total Rod Length	Package Length	1/4" Glow Rod Kits
7-36-23T	24'	6'	Three 6' X 1/4" Rods, Two 3' X 1/4" Rods One Bullet Nose with Eyelet, One Hook
7-63T	18'	3'	Six 3' X 1/4" Rods One Bullet Nose with Eyelet, One Hook
7-34T	12'	4'	Three 4' X 1/4" Rods One Bullet Nose with Eyelet, One Hook


3/16" DIAMETER GLOW RODS

Minimum Bend Radius: 4"

More Flexible For Short Runs Or
Use In Limited Space

Tensile/Pull Strength: 500 lbs

Part Number	Total Rod Length	Package Length	3/16" Glow Rod Kits
7S-45T	20'	5'	Four 5' X 3/16" Rods One Bullet Nose with Eyelet, One Hook
7S-35T	15'	5'	Three 5' x 3/16" Rods One Bullet Nose with Eyelet, One Hook
7S-718T	10.5'	18"	Seven 18" X 3/16" Rods One Bullet Nose with Eyelet, One Hook



What Size Do You Need?

Flexibility Increases As Rod Diameter Decreases

- 1/4" for long spans requiring greater rigidity
- 3/16" for short spans or in limited space
- 5/32" for making tight turns

Using the same size ferrules (#8-32), different diameter rods can be used together in any combination for ultimate on-the-job customization.



5/32" DIAMETER GLOW RODS

Smallest Diameter Offers Extreme Flexibility
With High Strength

Minimum Bend Radius: 3.5"

Tensile/Pull Strength: 300 lbs

Part Number	Total Rod Length	Package Length	5/32" Glow Rod Kits
7SS-36T	18'	6'	Three 6' X 5/32" Rods One Bullet Nose with Eyelet, One Hook
7SS-6	6'	*	One 6' X 5/32" Rod with Permanently Mounted Bullet Nose with Eyelet On Each End of Rod

* Single rods shipped with hanging tag, not in clear plastic kit tube



7SS-36T



7SS-6

Permanently mounted bullet nose on each end.

COMBO GLOW ROD KITS

A Variety Of Rod Sizes And Accessories For Greater Versatility On The Job

Part Number	Total Rod Length	Package Length	Installer's Kit
7-8-IK	35'	6'	Two 1/4" X 5' Rods, Two 1/4" X 2.5' Rods, Four 3/16" X 5' Rods Two Bullet Nose with Eyelet, Two Hooks, One Whisk



7-8-IK

Part Number	Total Rod Length	Package Length	Deluxe Kit
7S-65K	30'	6'	Six 3/16" X 5' Rods One Bullet Nose with Eyelet, One Hook, One Whisk, One Ball Chain Bullet Nose



7S-65K

Part Number	Total Rod Length	Package Length	Versa Kit
7-8VK	34'	6'	Two 1/4" X 6' Rods, Two 3/16" X 5' Rods, One 5/32" X 6' Rod One 5/32" X 6' Rod - Permanently Mounted Bullet Eye On Each End One Hook, One Whisk



7-8VK

GLOW ROD ACCESSORIES

To Handle Any Wiring Job

Part Number	Glow Rod Accessories
7-00A	Bullet Nose with Eyelet
7-01A	Hook
7-02A	Bullet Nose with Ring
7-03A	Whisk
7-04A	Ball Chain Bullet Nose
7-05A	Magnet
7-06AK	Accessory Kit




Accessory Kit
Hook
Magnet
Whisk
Ball Chain
Bullet Nose with Ring
Bullet Nose with Eyelet



Magnet
Retrieve Ball Chain



Hook
Grasp and retrieve



Bullet Nose with Ring
Pull line or grab with hook



Bullet Nose with Eyelet
Attach pull line to rod



Whisk
Guide rod; avoid obstacles



Ball Chain Bullet Nose
Use with Magnet for retrieval