

Product data sheet

Specifications



Rack PDU, Metered, 2U, 30A, 120V, (16) 5-20



AP7802B

Overview

Lead time Usually in Stock

Main

| | |
|---------------------------|--|
| Product or Component Type | PDU |
| PDU Type | Metered |
| Cord length | 12 ft (3.7 m) |
| Number of cables | 1 |
| Provided Equipment | Cord retention bracket(s) Installation guide Rack Mounting brackets User Manual |

Complementary

| | |
|--------------------------|-----------------------|
| Input Voltage | 100 V 120 V |
| Height | 3.5 in (8.8 cm) |
| Width | 17.5 in (44.4 cm) |
| Output Voltage | 120 V |
| Depth | 4.4 in (11.2 cm) |
| Net Weight | 7.41 lb(US) (3.36 kg) |
| mounting location | Front Rear |
| Mounting preference | No preference |
| Input Plug Type | NEMA L5-30P |
| Mounting Mode | Rack-mounted |
| Rack units | 2U |
| Mounting position | Horizontal |
| Line Rated Current | 24 A |
| Input current limits | 30 A |
| Load Capacity | 2880 VA |
| Input Frequency | 50/60 Hz |
| Outlet type and quantity | 16 NEMA 5-20R |

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|--|--|
| Product Certifications | cUL Listed CSA UL Listed |
| Standards | FCC Part 15 class A ICES-003 UL 60950 |
| Ambient Air Temperature for Operation | 23...113 °F (-5...45 °C) |
| Relative Humidity | 5...95 % |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | -13...149 °F (-25...65 °C) |
| Storage Relative Humidity | 5...95 % |
| Storage altitude | 0...50000 ft (0.0000000000...15240.0000000000 m) |

Ordering and shipping details

| | |
|--------------------------|--------------|
| GTIN | 731304331476 |
| Country of origin | IN |

Packing Units

| | |
|-------------------------------------|----------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.5 in (14 cm) |
| Package 1 Width | 14.5 in (36.8 cm) |
| Package 1 Length | 20.0000000000 in (50.8 cm) |
| Package 1 Weight | 11.93 lb(US) (5.41 kg) |

Contractual warranty

| | |
|-----------------|---------------------------|
| Warranty | 2 years repair or replace |
|-----------------|---------------------------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Lead Free

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

Image of product / Alternate images

Alternative



