

SONANCE


VISUAL EXPERIENCE DATA SHEET

VX52R UTL

INTERNATIONAL TECHNICAL SPECIFICATIONS

SKU	VX52R UTL 93654 - Pair
Tweeter	1" (25mm) cloth dome, Ferrofluid-cooled, acoustic back chamber
Woofer	5.25" (130mm) Anodized aluminum cone, rubber surround
Frequency Response	55Hz - 20kHz +/-3dB
Impedance	8 ohms nominal; 6 ohms minimum
Power Handling (RMS)	5 watts minimum; 100 watts maximum
Sensitivity (2.83V/1m)	89dB SPL
Round Micro Trim Grille (Dia)	9.62" (244.4mm)
Round Trimless Grille (Dia)	9.28" (235.6mm)
Square Micro Trim Grill (WxH)	9.62" x 9.62" (244.4mm x 244.4mm)
Square Trimless Grille (WxH)	9.28" x 9.28" (235.6mm x 235.6mm)
Speaker (Dia)	9.17" (232.8mm)
Speaker Mounting Depth (D)	1.41" (35.7mm)
Cut-Out Dims (Dia)	8.25" (210mm)
Product Weight (w/o Grille)	1.96 lbs (0.89kg) Each
Product Only Weight (w/ Grille)	2.34 lbs (1.06kg) Each
Shipping Weight	7.1 lbs (3.22kg)


DIMENSIONAL DRAWINGS



Front View



Side View



Back View