


WINDFLOWER

FR-W1815-80L

80" Ceiling Fan

MODERN FORMS SMART FANS



PRODUCT DESCRIPTION

As bold and beautiful as a classic Holland windmill, this contemporary twelve-blade design is perfect for mid-sized and larger spaces with its 60 inch or 80 inch blade sweeps. Control everything from the palm of your hand with our Wi-Fi-connected Modern Forms app- no one else in the industry can match this combination of style and intuitive technology. Available in three sleek finishes, Windflower makes life easier and more beautiful every day.

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes RF wall control
- Optional remote control sold separately
- Compatible with Modern Forms app

AIRFLOW/ENERGY EFFICIENCY

Weighted-Average/High Airflow CFM:	7690/10223
Weighted-Average/High Energy Use (W):	34/51
Estimated Yearly Energy Cost (\$):	10
Weighted-Average/High Efficiency (CFM/W):	227/200
Max RPM:	85

ORDER NUMBER

Model	Housing	Blade
FR-W1815-80L	OB Oil Rubbed Bronze	DW Dark Walnut
	GH Graphite	WG Weathered Gray
	MB Matte Black	DK Distressed Koa

Example: FR-W1815-80L-OB/DW

For 2700K add "-27" ; for 3500K add "-35" before the finish: FR-W1815-80L270BDW

***Results may vary based on application and surroundings.**

***This fan comes uni-pack - blade select options are not available**

The Modern Forms app synchronizes seamlessly with smart home devices you already own



modernforms.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

SPECIFICATIONS

Construction:	Aluminum, ABS
Blade:	15° Pitch, 80" sweep
Downrod:	.75"W x 6"H included
Mounting Slope:	Up to 30°
Wire:	80"
Hanging Weight:	42 lbs
Total Power:	74.5W
Standards:	UL/cUL Wet Location listed, Title 24 JA8-2016 Compliant, Title 20
Motor Type:	168 x 30 sensorless DC motor

WIRELESS PERFORMANCE

Remote Pairing Distance:	Up to 30 ft from fan
Wi-Fi Range:	Up to 150 ft*

LUMINAIRE PERFORMANCE

Light Source:	LED
Light Wattage:	23.5W
Lumens/Delivered Lumens:	2041/1080
Dimming:	Integrated
CRI:	90
Color Temperature:	3000K (2700K/3500K options available)
Rated Life:	50,000 hours






WINDFLOWER

FR-W1815-80L

80" Ceiling Fan

MODERN FORMS
SMART FANS

OPTIONAL ACCESSORIES

<p>Bluetooth Wall Control</p>		<p>F-WCBT</p>	<p>WT White</p>	<p>Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.</p>
<p>Bluetooth Remote Control</p>		<p>F-RCBT</p>	<p>WT White</p>	<p>Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Modern Forms Smart Fans. Includes easy-to-install wall cradle and batteries.</p>
<p>Downrod</p>		<p>XF-12 12IN XF-18 18IN XF-24 24IN XF-36 36IN XF-48 48IN XF-60 60IN XF-72 72IN</p>		<p>All our downrods are .75 (in) and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.</p>
<p>Downrod Couplers</p>		<p>XF-I</p>		<p>Connects two downrods together.</p>
<p>Sloped Ceiling Kit</p>		<p>XF-SCK</p>		<p>Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.</p>

Examples: Wall Control: **F-WCBT-WT**, Remote Control: **F-RCBT-WT**, Downrod: **XF-12-BN**, Downrod Coupler: **XF-I-MB**, Sloped Ceiling Kit: **XF-SCK-MW**

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire