



DARE TO BE BOLD

TREVERKCHIC™

COLORBODY™ PORCELAIN

TRUEDGE™ | REVEAL IMAGING®

MARAZZI 

DARE TO BE BOLD™



TREVERKCHIC™



AFRICA

The exemplary rendition of natural fine wood graining and contemporary colorations in Treverkchic by Marazzi USA elevates its standing in the wood-look porcelain hierarchy. Authentic visuals and textures translate the warmth of hand-crafted wood to easy-care porcelain.

ITALIANO

suite
man clothing



FRANCESE



AFRICA



TREVERKCHIC™

COLORBODY™ PORCELAIN

TRUEDGE™ | REVEAL IMAGING®

FLOOR TILE



Africa



Francese



Italiano



Americano

USAGE




Floors	Walls	Countertops
F	W	C

TREVERKCHIC™

COLORBODY™ PORCELAIN

TRUEDGE® | REVEAL IMAGING®

SIZES

	Thickness	Sq. Ft./ Carton	Pieces/ Carton
 12 x 48 Floor Tile	(11-5/8" x 46-15/16") (29.56 cm x 119.30 cm)	3/8"	11.40
 8 x 48 Floor Tile	(7-3/4" x 46-15/16") (19.71 cm x 119.30 cm)	3/8"	15.18
 6 x 48 Floor Tile	(5-3/4" x 46-15/16") (14.71 cm x 119.30 cm)	3/8"	15.12

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	■
Wet & Level - Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	


A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit marazzitile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

	12 x 48	8 x 48	6 x 48
Africa	MH2S	MH2Y	MH34
Americano	MH2P	MH2V	MH31
Francese	MH2N	MH2U	MH30
Italiano	MH2M	MH2T	MH2Z

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%.)	 High Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.



All or select items within this series meet the requirements for these qualifications. For more information visit marazzitile.com.

PHOTOGRAPHY INDEX:

Cover

Treverkchic™ in Italiano 12 x 48, 8 x 48 & 6 x 48

Page 2-3

Treverkchic™ in Africa 8 x 48

Page 4

Treverkchic™ in Americano 12 x 48

Page 5 Top

Treverkchic™ in Francese 8 x 48

Page 5 Bottom

Treverkchic™ in Africa 8 x 48

MARAZZI 

DARE TO BE BOLD™

7834 C.F. Hawn Freeway
Dallas, Texas 75217

www.marazzitile.com
contact@marazzitile.com

©2018 Marazzi | 07.18 | MZBRO123 Treverkchic™ Brochure

Color and other aesthetic features shown are as close as the limitation of the printing process will allow. We have tried to make this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time, without notice, in colors, materials, packaging, specifications and availability. Since some information may have been updated since time of printing, please check with Marazzi Customer Service for details.