

# Eaton LE215AB00T

Catalog Number: LE215AB00T

Eaton Cooper Power series loadbreak elbow, 200 A, Std V:15 kV, Max phase-to-ground:8.3 kV, AC 1 min:34 kV, DC 15 min:34 kV, Impulse:95 kV, Max corona:11 kV, Test:Yes, 0.61 inch, 0.97 inch, 15.5 mm, 24.6 mm, No connector, 20 pack



## General specifications

Product Name	Catalog Number
Eaton Cooper Power series loadbreak elbow	LE215AB00T
	UPC
	194006007832
Product Length/Depth	Product Height
15.25 in	18 in
Product Width	Product Weight
15.25 in	3.131 lb
Compliances	Certifications
Not Applicable	IEEE 386

## defaultTaxonomyAttributeLabel

### Type

Loadbreak elbow

### AC 1 minute voltage withstand

34 kV

### Basic impulse level

95 kV

### Cable insulation diameter - max

0.97 in

### Cable insulation diameter - min

0.61 in

### Stranded or compressed conductor size

No connector

### Current rating

200 A

### DC 15 minute withstand

34 kV

### Maximum rating phase-to-ground

8.3 kV

### Corona voltage level - min

11 kV

### Standard pack

20 pack

### Standard voltage class

15 kV

## Resources

### Specifications and datasheets

[Eaton Specification Sheet - LE215AB00T](#)

[Line installation and protective equipment specifiers guide](#)