

# Product data sheet

Specifications



## APC NetShelter Switched Rack PDU, 0U, 5.0kW, 200V and 208V, 30A, 21 C13/C15 and 3 C19/C21 outlets

APDU9941

### Overview

|           |                  |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

### Main

|                           |                                                              |
|---------------------------|--------------------------------------------------------------|
| Color                     | Black                                                        |
| Product or Component Type | PDU                                                          |
| PDU Type                  | Switched                                                     |
| Cord length               | 9.8 ft (3 m)                                                 |
| Number of cables          | 1                                                            |
| Provided Equipment        | Installation guide<br>Rack Mounting brackets<br>Safety guide |

### Complementary

|                             |                      |
|-----------------------------|----------------------|
| Input Voltage               | 208 V<br>200 V       |
| Height                      | 72.008 in (1829 mm)  |
| Width                       | 2.2 in (55 mm)       |
| Output Voltage              | 200 V<br>208 V       |
| Depth                       | 1.8 in (46 mm)       |
| Product Weight              | 18.7 lb(US) (8.5 kg) |
| Mounting Location           | Side                 |
| Mounting preference         | No preference        |
| Input Plug Type             | NEMA L6-30P          |
| Mounting Mode               | Not rack-mountable   |
| Rack units                  | 0U                   |
| USB compatible              | No                   |
| Mounting position           | Vertical             |
| Communication Port Protocol | SNMP<br>Redfish      |
| Line Rated Current          | 24 A                 |
| Max line current            | 30 A                 |
| Input current limits        | 30 A                 |
| Load Capacity               | 4992 VA              |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                            |                       |
|----------------------------|-----------------------|
| Input Frequency            | 50/60 Hz              |
| Outlet type and quantity   | 21C13/C15<br>3C19/C21 |
| Communication Network Type | 10/100/1000BASE-T     |

## Environment

|                                       |                                          |
|---------------------------------------|------------------------------------------|
| Product Certifications                | cUL Listed<br>FCC part 15 class A<br>PSE |
| Standards                             | ICES-003                                 |
| Ambient Air Temperature for Operation | 23...140 °F (-5...60 °C)                 |
| Relative Humidity                     | 5...95 %                                 |
| Operating altitude                    | 0...10000 ft                             |
| Ambient Air Temperature for Storage   | -13...149 °F (-25...65 °C)               |
| Storage Relative Humidity             | 5...95 %                                 |
| Storage altitude                      | 0...50000 ft (0...15240 m)               |

## Ordering and shipping details

|                   |              |
|-------------------|--------------|
| GTIN              | 731304356264 |
| Country of origin | IN           |

## Packing Units

|                        |                      |
|------------------------|----------------------|
| Unit Type of Package 1 | PCE                  |
| Nbr. of units in pkg.  | 1                    |
| Package 1 Height       | 80.3 in (204 cm)     |
| Package 1 Width        | 4.9 in (12.4 cm)     |
| Package 1 Length       | 6.5 in (16.5 cm)     |
| Package weight(Lbs)    | 22.05 lb(US) (10 kg) |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 36 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 2 642 kg CO2 eq.                              |
| Carbon footprint of the manufacturing phase [A1 to A3] | 56 kg CO2 eq.                                 |
| Carbon footprint of the distribution phase [A4]        | 0.2 kg CO2 eq.                                |
| Carbon footprint of the installation phase [A5]        | 2 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 2 580 kg CO2 eq.                              |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 4 kg CO2 eq.                                  |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                                                                        |
|----------------------------------------|----------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                    |
| Packaging without single use plastic   | No                                                                                     |
| SCIP Number                            | 31346aed-552c-4a16-81d9-e683a383b6da                                                   |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a>                                                 |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a> |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                               |                                                                                                                                                                                                                  |
|-------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in % | 71                                                                                                                                                                                                               |
| Circularity Profile           | <a href="#">End of Life Information</a>                                                                                                                                                                          |
| Removable battery             | Yes                                                                                                                                                                                                              |
| Take-back                     | No                                                                                                                                                                                                               |
| WEEE Label                    |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Image of product / Alternate images

Alternative

---



