

# Reign



## Colors



Cross Ivory  
VTL RGCI



Cross Cream  
VTL RGCC



Cross Gray  
VTL RGCG



Vein Ivory  
VTL RGV I




Vein Cream  
VTL RGV C




Vein Gray  
VTL RGV G

## Sizes




48" x 48" x 9.5mm Rectified



40" x 40" x 8.5mm Rectified



24" x 48" x 9.5mm Rectified



24" x 24" x 9.5mm Rectified



12" x 24" x 9.5mm Rectified

## Field Tiles\*

SIZE	ACTUAL	THICKNESS	FINISH
48" x 48" Rectified	47.24" x 47.24"	9.50mm	Matte/Natural
40" x 40" Rectified	39.37" x 39.37"	8.50mm	Matte/Natural
40" x 40" Grip Rectified	39.37" x 39.37"	8.50mm	Bush-Hammered
40" x 40" Semi-Rectified	39.37" x 39.37"	8.50mm	Light or Semi-Polished
24" x 48" Rectified	23.62" x 47.24"	9.50mm	Matte/Natural
24" x 48" Semi-Rectified	23.62" x 47.24"	9.50mm	Light or Semi-Polished
24" x 24" Rectified	23.62" x 23.62"	9.50mm	Matte/Natural
24" x 24" Grip Rectified	23.62" x 23.62"	9.50mm	Bush-Hammered
24" x 24" Semi-Rectified	23.62" x 23.62"	9.50mm	Light or Semi-Polished
12" x 24" Rectified	11.81" x 23.62"	9.50mm	Matte/Natural
12" x 24" Grip Rectified	11.81" x 23.62"	9.50mm	Bush-Hammered

\* Not all sizes/trims are available in all colors and finishes, scan QR code for product details.

## Product Characteristics

	MATTE/NATURAL BUSH-HAMMERED LIGHT OR SEMI POLISHED
Breaking Strength (ASTM C648 or ISO 10545-4)	≥ 1300N
Chemical Resistance (ASTM C650 or ISO 10545-13)	A-HA-LA
DCOF	≥ 0.42
Deep Scratch Resistance - Unglazed (ISO 10545-6)	N/A
Frost Resistance (ASTM C1026 or ISO 10545-12)	Resistant
Mohs Hardness - EN101	6
Water Absorption (ASTM C373 or ISO 10545-3)	≤ 0.1%
Certifications	N/A
Country of Origin	Italy
Shade Variation Code	V2



Made in Italy



Import



V2 Slight Variation



DCOF: ≥0.42

## Mosaics & Coordinating Trims\*

SIZE	ACTUAL	FINISH
11" x 13" Hexagon Mosaic Rectified	11.02" x 12.60"	Matte/Natural
2" x 2" Mosaic Rectified	11.81" x 11.81"	Matte/Natural
24" x 48" Rule Decorative Rectified	23.62" x 47.24"	Matte/Natural
3" x 24" Bullnose Rectified	2.56" x 23.62"	Matte/Natural

Recommended Grout Joint: 1/8" - Rectified  
3/16" - Non Rectified

## Application\*\*

		WALL	FLOOR
Interior	Residential	•	•
Interior	Commercial	•	•
Interior	Heavy Commercial	•	
Exterior	Residential/Commercial	•	•

\*\* These recommendations are not defined by ANSI Standards

## Material

Glazed Color-Body Porcelain



Scan QR Code for  
Product Information and  
Installation Images

# Request samples.

www.vitlsurfaces.com  
samples@vitlsurfaces.com

