



Introduction

The Atlona **VTP-800** is a Velocity System 8" touch panel for AV control and room scheduling. It features contemporary, refined styling for modern presentation environments with 1280×800 native resolution, and a capacitive glass surface that supports multi-touch and gesture interactions. This touch panel conveniently installs into a wall or furniture via a US two-gang opening. Also available is the optional AT-VTP-TMK tabletop mounting kit for placement on a meeting table or lectern. The VTP-800 features Power over Ethernet (PoE), enabling a single network connection for data and power. Setting up the touch panel is effortless as the AV control GUI is automatically uploaded from the Velocity System hardware or software server gateway during system configuration.

Applications

- **Meeting spaces, lobbies, hallways, and other settings in enterprise, government, and public institutions**
Velocity Touch Panels feature an appealing visual design that offers a complementary yet enhanced aesthetic for various environments.
- **Classrooms, lecture halls, and other instructional spaces**
Velocity Touch Panels can serve to provide a consistent GUI and user experience from room to room throughout a K-12 institution, as well as a university department, facility, or even the entire campus.

Key Features

Room scheduling and AV control touch panels

- Single, flexible touch panel platform that can be used for a variety of applications.
- Only need to stock a single panel to satisfy multiple requirements.

Fast streamlined setup

- Automatic network discovery and configuration by a Velocity System Gateway.
- Room scheduling and AV control GUIs are automatically loaded by a single configuration tool.

Fast streamlined setup

- Automatic network discovery and configuration by a Velocity System Gateway.
- Room scheduling and AV control GUIs are automatically loaded by a single configuration tool.

PoE

- Remotely powered via Power over Ethernet.
- Single cable network connection for data and power.

Proximity sensor

- Various actions can be configured for when users are close to the panel.
- Wakes up panel when user walks by or enters a room.

Additional Features

- Capacitive touch screen with 1280x800 resolution
- Supports multi-touch and gesture interactions
- Contemporary, refined styling and aesthetics
- Available in black or white
- Mounts into a standard US two-gang electrical junction box, wall opening, or furniture
- Freestanding placement also available with the optional AT-VTP-TMK tabletop mounting kit
- Energy-saving features including adjustable sleep timer
- Ambient light sensor with automatic brightness adjustment
- Configurable audio feedback available for button presses
- Gigabit Ethernet port

Specifications

Display		
Panel	Capacitive touch, 8” LCD, 1280 x 800	
Color Depth	8 bits per channel / 16.7 million colors	
Audio		
Microphone	Digital MEMS (MicroElectro-Mechanical Systems)	
Speaker	High-Fidelity, 2 W	
Sensors		
Electro-optical	Ambient light sensor	
Proximity	Advance “time-of-flight” sensor	
Power		
Type	PoE 802.3af compliant	
Dimensions	Inches	Millimeters
H x W x D	5.84 x 8.79 x 1.42	148 x 223.50 x 36
Wall, 2-gang, H x W x D	2.05 x 3.41 x 0.81	52.14 x 86.64 x 20.45
Weight	Pounds	Kilograms
Device	1.0	0.45
Certification		
Device	CE, FCC, RoHS/WEEE	