

PVC COATED ALUMINUM CONDUIT HUBS - ST

Features:


- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- ST available in 12 trade sizes from ½" through 6"
- Sealing sleeves on conduit side of hub
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes 1/2"- 2"
- For sizes 2½"- 6", the length of the sleeve extension(s) shall be at least 2"

Applications:

Calbond PVC Conduit Hubs are used to terminate conduit runs into electrical enclosures. PVC coating and internal urethane coating provide for superior corrosion protection. Electrical continuity is maintained across assembled joints.

Standards:

- NEC/CEC:
 - Class I, Division 2,
 - Class II, Division 1 & 2
 - Class III, Division 1 & 2
 - Class I, Zone 1, AEx e II
 - Class I, Zone 1, Ex e II
- All Screw-tight Hubs are manufactured in accordance with NEMA type enclosures 2, 3, 3R, 4, 4x, 11 & 12



Part Number	Trade Size (in)	A (in)	B (in)	C (in)	Max Wall Thickness (in)
PA0500STA1	½	1.84	2.00	1.31	0.125
PA0700STA2	¾	2.22	2.25	1.66	0.125
PA1000STA3	1	2.66	2.50	2.03	0.125
PA1200STA4	1¼	2.94	3.25	2.28	0.125
PA1500STA5	1½	3.19	3.50	2.53	0.125
PA2000STA6	2	3.75	4.25	3.09	0.125
PA2500STA7	2½	4.22	4.75	3.28	0.125
PA3000STA8	3	4.31	5.25	3.38	0.125
PA3500STA9	3½	4.38	5.50	3.44	0.125
PA4000STA10	4	4.44	6.25	3.50	0.125
PA5000STA11	5	4.94	7.50	4.00	0.125
PA6000STA12	6	5.00	8.50	4.00	0.125

All dimensions are for informational purposes only *Tolerances +/- 5%

