



You have chosen the Aimpoint Comp®, an advanced red-dot sight for the demanding sport of competitive shooting. Aimpoint Comp is developed from the demands of competitive shooters worldwide. Rough construction, parallax-free optics, state-of-the-art electronics and low weight makes Aimpoint Comp the natural choice for every quality minded shooter.

MOUNTING:

Aimpoint Comp is basically to be mounted with two 30 mm. rings or a uni-mount, on the front tube. To ensure repeatability and optimal adjustment area, be sure to follow the instructions for each mount properly. Before it is tightened, you will be able to rotate the sight in the rings so that the electronic device can be placed on which side You want ①.

WINDAGE AND ELEVATION ADJUSTMENT:

Aimpoint Comp has a circular sized adjustment area, with a diameter of 8.5 ft. at 100 yds. To adjust, unscrew the protection caps from the adjustment screws ②. The screws are equipped with a slot that fits i. e. a coin. Turn the adjustment screws until you reach the point of impact you prefer. Each click of the adjustment screw makes a 1/8 in. movement of the point of impact at 25 yds. The adjustment is centered when the sight leaves the factory, to provide maximum adjustment possibilities in every direction. Therefor do not adjust screws until the sight is mounted on your firearm.

LIGHT ADJUSTMENT AND BATTERIES:

Aimpoint Comp is equipped with a rotary switch with ten positions ③. One OFF-position and nine positions for different dot intensity settings. The first position is a EHI-position (Extra High Intensity) to be used in extreme bright conditions. The sight comes equipped with three mercury batteries SP 675 ④. In cold weather situations we recommend lithium or silveroxide batteries, which have better low temperature characteristics. Zink-air batteries are not recommended. Due to the need of air to work.

TECHNICAL DATA:

Optics: 100% parallax free, anti-reflex coated lens system.

Length: 4.3 in.

Weight: 4.7oz.

Dot diameter: 1.75 in. on 25 yds. (7 MOA)

or 2.5 in. on 25 yds. (10 MOA).

Battery life: *(Fresh batteries) 75-500 hours avg. (EHI, 7-15 hours continuous)

*The sight is packed with fresh batteries from factory.

Aimpoint, Inc. reserves the right to change or improve our products as we find necessary. This manual describes the product at the time of this publication.

Aimpoint

For USA and Canada:

580 Herndon Parkway
Suite 500,
Herndon, VA 220 70, USA
Phone (703) 471-6828
Fax (703) 689-0575

For all other countries:

Jägershillgatan 15
S-213 75 Malmö, Sweden
Phone +46 (0) 40 21 03 90
Fax +46 (0) 40 21 92 38