

# James

BY SONANCE

## CUBE SERIES DATA SHEET

### TECHNICAL SPECIFICATIONS

	<b>CUBE43</b>	<b>CUBE63</b>
<b>UOM</b>	Each	Each
<b>Tweeter</b>	(1) 0.75" (19mm) Aluminum Dome	(1) 1" (25mm) Neodymium Beryllium
<b>Woofers</b>	(1) 4" (101mm) Aluminum Active (1) 4" (101mm) Aluminum Passive	(1) 6.5" (165mm) Aluminum Active (1) 6.5" (165mm) Aluminum Passive
<b>Frequency Response</b>	70Hz - 22kHz +/-3dB	50Hz - 25kHz +/-3dB
<b>Impedance</b>	8 ohms nominal	8 ohms nominal
<b>Recommended Power</b>	50 watts minimum; 100 watts maximum	25 watts minimum; 150 watts maximum
<b>Sensitivity (2.83V/1m)</b>	86dB SPL	90dB SPL
<b>Finish Options</b>	Gloss Black, Gloss White, Custom	Gloss Black, Gloss White, Custom
<b>Overall Dims (WxHxD)</b>	4.5" x 4.5" x 4.5" (114mm x 114mm x 114mm)	7.5" x 7.5" x 7.5" (190mm x 190mm x 190mm)

### DIMENSIONAL DRAWINGS

