

CRC® Heavy Duty Silicone Lubricant



Product Description

Lubricates and eliminates squeaking and binding caused by friction. Film is clean and highly resistant to water. Use on nylon, rubber, metal & non-metal surfaces.

Applications

Wood, metal and rubber surfaces. Use in moist and harsh environments. Not for use as an appearance cleaner or on paint.

Identification

Item Number / Case Number	1003743 / 1003742
Legacy Number	05174
Unit Package Description	16 Ounce Aerosol
Net Fill	11 wt oz
UPC Code	078254051741
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12

Properties

Appearance	Clear Colorless Liquid
Base Type	Silicone
Boiling Point (F/C)	132.9°F / 56.1°C
Dielectric Strength	350 Volts/Mil
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
Evaporation Rate	Fast
Flash Point (F/C)	<0°F / <-18°C
Flammability LEL % / UEL %	1.1 / 12.8
Flammability Class - CPSC	Extremely Flammable
NSF Category Code	N/A
Odor	Solvent
Plastic Safe	No
Propellant	Hydrocarbon
Restricted From Sale In:	
Solubility	Water - Slightly soluble
Spec Gravity Concentrate	0.748
Vapor Density	>1 (air = 1)
VOC % (Consumer Product def)	59.5
VOC Category	Silicone Based Multi-Purpose Lubricant
Working Temp (F/C)	-40 to 400°F / -40 to 204.4°C

Sizes

7.5 wt oz	05074
11 wt oz	05174



For more information: 800-556-5074 • cxus@crcind.com • crcindustries.com

CRC Industries, Inc. is a global leader in the production of specialty products and formulations for the do-it-yourself and maintenance professional, serving the automotive, industrial, electrical, marine, heavy truck, hardware, and aviation markets.