


## K1403 High Performance Infrared PoE+ Illuminator 850nm





## **FEATURES**:

- PoE with Cat5e cable up to 45M (147 ft)
- High Power IR LED x 12pcs
- Brightness Adjustable (10 steps)
- Delay time Adjustable (2-30 sec)
- External trigger mode (NO or NC) Selectable (Trigger in and Trigger out)
- Light ON and light OFF: ambient brightness adjustable
- ●IR Remote control
- IK 10 Vandal resistance approved
- ■IP68 waterproof
- AC24V / DC48-56V/PoE+ (802.3at)

## **SPECIFICATIONS:**

ITEM	K1403
Quantity of LED	3W high power LEDs X 12pcs
Wavelength	850nm
Beam angle	10 \ 30 \ 60 \ 120 degrees
IR distance	45 m ( 147 ft)
Day/night switch	Master Mode: auto on/off by Light Sensor;
	Slave Mode: on/off by Trigger Input
Voltage	AC24V / DC48-56V/
	PoE+ (802.3at)
Power consumption	22 W
	802.3at PoE+ class 4
Trigger I/O	Trigger Input: NC/NO selectable (TTL)
	Trigger Output :NC/NO selectable (Dry Contact)



**ETHERNET SERIES** 

Front panel	Vandal PC
Housing	Aluminum
Bracket	Wall mount bracket
Working temperature	$-30^{\circ}$ C ~ + $60^{\circ}$ C (-22 to 140°F)
Water Proof	IP68
Vandal Proof	IK10
Color	Black
Dimension	140 x 150 x 57 mm (without bracket)
Net weight	1.2kg (without bracket)

## **Dimension:**

