

M5300-PM

Premium Home Theater Power Manager

Improves picture and sound quality, monitors, and reduces cross contamination

- Clean power level 4
- Improves picture and sound quality by eliminating noise across the entire AC bandwidth. 40% more efficient at eliminating noise than Clean Power Level 3
- AVM (Automatic Voltage Monitoring)
- Protects equipment agains prolonged over /under voltages by disconnecting the power and reconnecting it when safe when safe power returns
- High current outlets
- 2 outlets for equipment with high power demands (Amps / Subwoofers)
- USB Charger
- 1 front panel 500mA USB charger

M5300-PM Premium Home Theater Power Manager

LIMITED $5,000,000 CONNECTED EQUIPMENT PROTECTION POLICY* *See warranty for details

Features

- Clean power level 4
- Improves picture and sound quality by eliminating noise across the entire AC bandwidth. 40% more efficient at eliminating noise than Clean Power Level 3
- AVM (Automatic Voltage Monitoring)
- Protects equipment agains prolonged over /under voltages by disconnecting the power and reconnecting it when safe when safe power returns
- High current outlets
- 2 outlets for equipment with high power demands (Amps / Subwoofers)

Specifications

Voltage Protection Rating (UL 1449 3rd Edition, 3,000A)	500V
Single Pulse Energy dissipation	2125 Joules
Peak Impulse Current	72,000 amps
LAN - Wires Protected	8–Wires
LAN - clamping Level	60V ± 5V
Coax - Shielded	Yes
Coax - Insertion Loss	< 0.5 db
Coax - HD 1080 i/p Ready	Yes
Coax - Frequency Range	0 MHz - 2.2 GHz
Coax - Connection	Female nFi, Gold plated
Coax - Clamping Level	75V
Coax - Bidirectional	Yes

Other Specifications

Family	PM Series
Line Voltage	120 (Volts)
Number of Outlets	11
Number of isolated Banks	5

Outlet Descriptions	1 (always on, linearly filtered outlet, front panel) 4 (always on, linearly filtered outlets, rear panel) 4 (switchable, linearly filtered outlets, rear panel) 2 (switchable high current outlets, rear panel)
Rack Mountable	Yes
Rack Ears Included	Yes
Front Panel Meter(s)	1 Voltmeter, 1 Ammeter
Front Media Lights(s)	No
Control	On/Off control of switched outlets through front panel power button or rear panel DC trigger
Voltage Regulation	No
Compliance	cCSAus
USB Charging	1 front panel 500mA USb charger. May not recognize all devices
Low Voltage Trigger	12 V, In/Out
AC Power Cord	10 ft. detachable
Dimensions	17" W x 12.75" H X 3.5" H (4.1" Including feet)
Weight	12.8 lbs

AC Protection Technology	Protect or Disconnect Automatic Voltage Monitoring L-N, L-G,N-G Protection Modes Thermal fusing
Under-voltage Shutoff	90 VAC ± 2 VAC
Over-Voltage Shutoff	142 VAC ± 8 VAC
Maximum Current Rating	15 (Amps)
Initial Clamping Level	200V Peak
Filtration Technology	LiFT
Filtration Rating	Bank 1: Up to -86 db (100 KHz _2 MHz) Bank 2: Up to -91 db (100 KHz _2 MHz) Bank 3: Up to -81 db (100 KHz _2 MHz) Bank 4: Up to -100 db (100 KHz _2 MHz) Bank 5, High Current Outlets: up to -81 db (100 KHz _2 MHz)
Signal Line Protection	2 LAN, 1 Tel, 3 Cable/Satellite
Length	20.3"
Width	10.3"
Height	24"
Weight	19.55 (Lbs)
Unit of Measure	Each
UPC	050616008167
Master Pack Quantity	1
Warning	Cancer and Reproductive Harm www.P65Warnings.ca.gov



Niceforyou.com

Nice

©2024 Nice North America LLC. All rights reserved.
All other products or name brands are trademarks of their respective holders.

1146541634 Rev-A 09/2024