



Damp2Dry[®] COMMERCIAL DEHUMIDIFIER

140 PINT, 310 PINT

	3PACD140	3PACD250
UPC CODE	842149002442	842149002459
WATER REMOVAL CAPACITY (90°F, 90% RH)	140 pts./Day (17.6 gal./Day)	310 pts./Day (38.8 gal./Day)
WATER REMOVAL CAPACITY (80°F, 60% RH)	75 pts./Day (9.4 gal./Day)	165 pts./Day (20.6 gal./Day)
RATED POWER (W)	610	1130
RATED CURRENT (A)	5.5	10.2
IEF (L/KWH)	2.42	2.88
DEFROST TYPE	Ventilated	Ventilated
AIR VOLUME (CFM)	190	515
OPERATING TEMPERATURE	40°F - 104°F	33°F - 110°F
REFRIGERANT	R32	R32
WASHABLE AIR FILTER	Yes	Yes
POWER CORD LENGTH (ft.)	25	25
DRAIN HOSE LENGTH (ft.)	20	20
STACKABLE FOR STORAGE	Yes, up to 2 units	Yes, up to 2 units
UNIT DIMENSIONS (W×H×D) (in.)	19 × 24 × 18.75	23 × 33 × 22
PKG. DIMENSIONS (W×H×D) (in.)	23.5 × 25.25 × 20.25	27 × 34 × 25
WEIGHT (Net/Gross) (lbs.)	73 / 79	126 / 138
CONTAINER QTY. (20'/40'/40' HQ)	126 / 267 / 356	54 / 108 / 162
OUTLET CONFIGURATION	 15A - 115V	 15A - 115V
SELLABLE IN CALIFORNIA	Yes	No



3PACD250



3PACD140

FEATURES

- Durable polyethylene housing and telescoping metal handle
- Direct-to-drain hose access with 20 ft. ejector pump hose, with quick-connect technology to for easy install
- Low grain performance achieves low specific humidity levels for with superior moisture control in challenging environments
- Automatic defrost prevents evaporator from freezing
- Variable speed fan motor enables precise airflow control, resulting in optimized moisture extraction
- Digital, soft-touch control pad
- Advanced wireless controls with the smartphone app
- Easy-access slide-out, washable high-grade steel filter (SUS304)
- Ideal for any area affected by humidity from flooding, water leakage, or natural disasters



PUMPS WATER
18 FT. VERTICALLY



HIGH RATE OF
WATER REMOVAL



AUTOMATIC
DEFROST



WIRELESS
CONTROLS