

DRUMSAVER™ INSERT FOR STEEL DRUMS

PRODUCT DESCRIPTION: The 55 is an accordion-style, seamless, vacuum-formed insert for 55-gallon open-head steel drums. Flexible accordion-pleat side-walls accommodate variations in drum heights, a common issue with reconditioned drums. The 55 is molded from FDA-approved low-density polyethylene. A contoured lip snaps over the top bead to prevent leakage between the insert and the drum wall, while also providing easy drum closure using a standard ring and bolt or lock assembly.

Insert Specifications

MATERIAL USED

Low-density polyethylene

INSERT DIMENSIONS

Diameter: 22.5" (+0.25"/-0")

Height: 33" - 34.5"

Average thickness: 15 mil (+/-10%)

WEIGHT

1.4 lbs. (+/-10%)

SIDE-WALL DESIGN

Accordion

TEMPERATURE PARAMETERS

High (momentary): 175° (195°)F

Low: -40° F

Packaging Specifications

CARTON WEIGHT

35 lbs.

CARTON DIMENSIONS

Length: 35.25"

Width: 21"

Height: 14.50"

QUANTITY/CASE

20

PACKAGING STYLE

Rolled

TYPICAL APPLICATIONS: The 55 is designed for reconditioned drums because the accordion-style side wall design allows for a range of drum heights. The 55 is perfect for mixing, pumping and storing all liquids, powders and pastes that can be contained in low-density polyethylene. Examples include chemicals, inks, adhesives, greases, paints, coatings, silicones, and food. Can be used when rolling drums.

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.

DISTRIBUTED BY:



REF NO.:

DWG50009

DESCRIPTION:

55 Gallon 15 mil LDPE Drumsaver Insert, Accordion Style