



VERSACOOLER™ VANDAL RESISTANT BI-LEVEL DRINKING FOUNTAIN, WITH VANDAL RESISTANT BUBBLER REFRIGERATED & ELECTRONIC BOTTLE FILLER, VERSAFILTER III FILTER
MODEL PGV8FEBFSL-BRB-FVF

Suggested Specification

Model PGV8FEBFSL-FVF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Shall include the VersaFiller® with contactless activation and laminar flow; each fountain shall have a single vandal resistant push button to activate the manual flow of water for the cooler. Bottle Filler alcove and cabinet finish shall be stainless steel. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall operate between 20 and 100 PSI. Cabinet finish shall be brushed stainless steel. Cabinet shall have galvanized steel screens to prevent objects from being inserted into ventilation panels or underside of unit. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

- | | |
|----------------------|---|
| Features: | • Universal design: high right or high left |
| | • Built-in 100 micron strainer stops particles before they enter the waterway |
| | • Waterways are Lead-Free in materials & construction |
| | • One-piece vandal resistant bubbler keyed into position |
| | • Vandal resistant fasteners |
| | • Galvanized steel louver and bottom screens |
| | • High efficiency cooling system |
| | • Stainless steel top and heavy duty galvanized steel frame |
| | • Contactless activation bottle filler with programmable auto shut off |
| | • Includes integral self-scouring waste drain |
| | • External access to stream height adjustment on lower VersaCooler fountain |
| | • External access to thermostat with tool activated OFF position |
| | • Filter located in top bottle filler for easy filter replacement with Tilt 'N Tether |
| | • Built-in filter monitor and bottle counter |
| | • Logos permanently formed into the alcove and stainless steel wrapper |
| • LED lighted alcove | |

Filtration System:	OASIS VersaFilter III, certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.
---------------------------	---

Power:	115 Volts, 60 Hz
---------------	------------------

Activation By:	Contactless Sensor on Bottle Filler and Manual Activation on Fountain
-----------------------	---

Mounting Type:	Wall Mounted
-----------------------	--------------

Chilling Option:	8.0 gph*
-------------------------	----------

Full Load Amps	5.0 amps
-----------------------	----------

Rated Watts	500
--------------------	-----

Approx. Net Weight	86 lbs
---------------------------	--------

Installation Location:	Indoor
-------------------------------	--------



Ships in one box.

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

Finishes

- Standard cabinet finish: Stainless steel

Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system. Bottle fillers, fountains, and electrical components are warranted for 12 months. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

MODEL: _____ QTY: _____

PROJECT: _____

CONTACT: _____

NOTES: _____

APPROVAL: _____ DATE: _____



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov



Specifications subject to change without notice



VERSACOOLER™ VANDAL RESISTANT BI-LEVEL DRINKING FOUNTAIN, WITH VANDAL RESISTANT BUBBLER REFRIGERATED & ELECTRONIC BOTTLE FILLER, VERSAFILTER III FILTER
MODEL PGV8FEBFSL-BRB-FVF

Accessories



OASIS VersaFilter III Replacement Cartridge

OASIS Item #041145-001

- Certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.



Cane apron

Stainless Steel Finish, OASIS Item #035174-003

- ADA Compliant Apron is needed when water cooler is not installed in an alcove or with right and left wing walls. OASIS Apron is to provide the mandatory 27" to floor ADA requirement.



[View all filters and accessories](#)

