

# Rigid/Intermediate Grade Conduit Fittings

## Conduit Clamps, Straps, Hangers

### CLAMPS – MALLEABLE IRON

#### Applications:

- To support rigid conduit and IMC to mounting surface

#### Options:

##### Description

- Hot dip galvanized ..... **Suffix HDG**

UL File No. E-184283



| Cat. # | Size   | Unit Qty. | Wt. Lbs. Per 100 |
|--------|--------|-----------|------------------|
| 510    | 1/2"   | 100       | 6                |
| 511    | 3/4"   | 50        | 8                |
| 512    | 1"     | 50        | 13               |
| 513    | 1 1/4" | 25        | 20               |
| 514    | 1 1/2" | 20        | 30               |
| 515    | 2"     | 10        | 64               |
| 516*   | 2 1/2" | 5         | 104              |
| 517*   | 3"     | 2         | 120              |
| 518*   | 3 1/2" | 2         | 150              |
| 519*   | 4"     | 2         | 220              |
| 520†   | 5"     | 1         | 380              |
| 521†   | 6"     | 1         | 690              |

\*Also for use with thin wall (EMT) conduit.

†Not UL Listed.

### CLAMPBACKS/SPACERS – MALLEABLE IRON

#### Applications:

- To provide space between conduit and mounting surface

#### Standard Materials:

- Stamped steel – 1/2" - 1 1/2"
- Malleable iron – 2" - 6"

#### Options:

##### Description

- Hot dip galvanized ..... **Suffix HDG**

UL File No. E-184283



| Cat. # | Size   | Unit Qty. | Wt. Lbs. Per 100 |
|--------|--------|-----------|------------------|
| CB1*   | 1/2"   | 25        | 8                |
| CB2*   | 3/4"   | 25        | 10               |
| CB3*   | 1"     | 25        | 12               |
| CB4*   | 1 1/4" | 25        | 21               |
| CB5*   | 1 1/2" | 25        | 42               |
| CB6    | 2"     | 10        | 40               |
| CB7    | 2 1/2" | 10        | 49               |
| CB8    | 3"     | 10        | 62               |
| CB9    | 3 1/2" | 10        | 91               |
| CB10   | 4"     | 10        | 110              |
| CB11†  | 5"     | 5         | 135              |
| CB12†  | 6"     | 5         | 225              |

\*Stamped steel.

†Not UL Listed.

### STRAPS – STEEL GALVANIZED

#### Applications:

- Used to secure rigid conduit or IMC to mounting surface

#### Two Hole

UL File No. E-184283



| Cat. # | Size   | Unit Qty. | Wt. Lbs. Per 100 |
|--------|--------|-----------|------------------|
| 496 2  | 3/8"   | 250       | 2                |
| 496 3  | 1/2"   | 150       | 2                |
| 496 4  | 3/4"   | 100       | 3                |
| 496 5  | 1"     | 50        | 7                |
| 496 6  | 1 1/4" | 50        | 8                |
| 496 7  | 1 1/2" | 50        | 10               |
| 496 8  | 2"     | 25        | 15               |
| 496 9  | 2 1/2" | 25        | 19               |
| 496 10 | 3"     | 25        | 23               |
| 496 11 | 3 1/2" | 25        | 93               |
| 496 12 | 4"     | 10        | 108              |

### CLAMPS – STEEL

#### Applications:

- To support rigid conduit and IMC to mounting surface

#### Heavy Gauge



| Cat. # | Size   | Unit Qty. | Wt. Lbs. Per 100 |
|--------|--------|-----------|------------------|
| 410    | 1/2"   | 100       | 5                |
| 411    | 3/4"   | 50        | 6                |
| 412    | 1"     | 50        | 11               |
| 413    | 1 1/4" | 50        | 13               |
| 414    | 1 1/2" | 25        | 20               |
| 415    | 2"     | 25        | 22               |
| 206    | 2 1/2" | 25        | 64               |
| 207    | 3"     | 25        | 71               |
| 208    | 3 1/2" | 10        | 120              |
| 209    | 4"     | 10        | 130              |

# Rigid/Intermediate Grade Conduit Fittings

## Conduit Clamps, Straps, Hangers

### CABLE AND CONDUIT HANGERS – STEEL

#### Certifications and Compliances:

- UL Listed

#### With Bolt



| Cat. #  | Conduit Sizes |               | Unit Qty. | Wt. Lbs. Per 100 |
|---------|---------------|---------------|-----------|------------------|
|         | EMT           | Rigid         |           |                  |
| 0B      | 1/2"          | 3/8" and 1/2" | 100       | 6                |
| 1B      | 3/4"          | 3/4"          | 100       | 6                |
| 2B      | 1"            | 1"            | 100       | 8                |
| 2 1/2 B | 1 1/4"        | -             | 100       | 10               |
| 3 B     | 1 1/2"        | 1 1/4"        | 100       | 11               |
| 4 B     | -             | 1 1/2"        | 100       | 16               |
| 5 B     | 2"            | 2"            | 50        | 23               |
| 6 B     | 2 1/2"        | 2 1/2"        | 50        | 29               |
| 7 B     | 3"            | 3"            | 25        | 31               |
| 8 B     | 3 1/2"        | 3 1/2"        | 10        | 38               |
| 9 B     | 4"            | 4"            | 10        | 38               |

### CABLE AND CONDUIT HANGERS – STEEL

#### Applications:

- Used to provide mechanical support to conduit and raceway systems

#### Certifications and Compliances:

- UL Listed
- cUL Listed

#### With Extruded Hole and Bolt



| Cat. #  | Description             | Unit Qty. | Wt. Lbs. Per 100 |
|---------|-------------------------|-----------|------------------|
| 0BX     | 3/8 and 1/2 RGD 1/2 EMT | 100       | 6                |
| 1BX     | 3/4 RGD 3/4 EMT         | 100       | 7                |
| 2BX     | 1 RGD 1 EMT             | 100       | 11               |
| 2 1/2BX | 1 1/4 EMT               | 100       | 10               |
| 3BX     | 1 1/4 RGD 1 1/2 EMT     | 100       | 13               |
| 4BX     | 1 1/2 RGD               | 100       | 16               |
| 5BX     | 2 RGD 2 EMT             | 50        | 17               |

### BEAM CLAMPS/INSULATOR SUPPORTS – MALLEABLE IRON

#### Standard Finish:

- Zinc plated


UL File No. E-184283



| Cat. # | Base Size | Jaw Opening | Max. Wt. Support | Tapped Holes | Unit Qty. | Wt. Lbs. Per 100 |
|--------|-----------|-------------|------------------|--------------|-----------|------------------|
| 528    | 3/4"      | 5/8"        | 50               | 10 - 24      | 25        | 14               |
| 529    | 3/4"      | 5/8"        | 50               | 1/4" - 20    | 25        | 13               |
| 530    | 1"        | 3/4"        | 60               | 10 - 24      | 25        | 23               |
| 531    | 1"        | 3/4"        | 100              | 1/4" - 20    | 25        | 24               |
| 532    | 1 1/2"    | 3/4"        | 80               | 5/16" - 18   | 50        | 47               |
| 533    | 2"        | 7/8"        | 100              | 3/8" - 16    | 25        | 81               |
| 534    | 2 1/2"    | 7/8"        | 200              | 1/2" - 13    | 25        | 155              |

#### Dimensions (in Inches):

| Cat. # | A    | B    | C    | Max. Beam Thickness |
|--------|------|------|------|---------------------|
| 528    | 1.10 | 1.23 | 0.56 | 1/2"                |
| 529    | 1.10 | 1.25 | 0.57 | 1/2"                |
| 530    | 1.37 | 1.37 | 0.67 | 5/8"                |
| 531    | 1.25 | 1.39 | 0.69 | 5/8"                |
| 532    | 1.47 | 1.57 | 0.91 | 7/8"                |
| 533    | 1.75 | 1.82 | 1.12 | 1"                  |
| 534    | 2.28 | 2.15 | 1.04 | 1"                  |



### BEAM CLAMPS/INSULATOR SUPPORTS – STEEL



| Cat. # | Base Size | Jaw Opening | Tapped Holes | Unit Qty. | Wt. Lbs. Per 100 |
|--------|-----------|-------------|--------------|-----------|------------------|
| 529 S  | 3/4"      | 5/8"        | 1/4" - 20    | 50        | 13               |

# Rigid/Intermediate Grade Conduit Fittings

## Conduit Clamps, Straps, Hangers

### CONDUIT CLAMPS – RIGHT ANGLE TYPE – HOT DIP GALVANIZED IRON

#### Applications:

- Right angle – to attach the conduit run at a 90° angle to a beam or structural member
- Parallel type – to attach the conduit run parallel to a beam or structural member



| Cat. #   | Size   | Load Rating Lbs. | Wt. Lbs. Per 100 |
|----------|--------|------------------|------------------|
| RAC50HD  | 1/2"   | 30               | 37               |
| RAC75HD  | 3/4"   | 50               | 40               |
| RAC100HD | 1"     | 60               | 42               |
| RAC125HD | 1 1/4" | 75               | 49               |
| RAC150HD | 1 1/2" | 80               | 54               |
| RAC200HD | 2"     | 100              | 71               |
| RAC250HD | 2 1/2" | 125              | 95               |
| RAC300HD | 3"     | 165              | 107              |
| RAC350HD | 3 1/2" | 200              | 120              |
| RAC400HD | 4"     | 330              | 131              |


### PARALLEL TYPE CONDUIT CLAMPS – ELECTROGALVANIZED IRON



| Cat. #    | Size   | Load Rating Lbs. | Wt. Lbs. Per 100 |
|-----------|--------|------------------|------------------|
| PARC50HD  | 1/2"   | 30               | 50               |
| PARC75HD  | 3/4"   | 50               | 53               |
| PARC100HD | 1"     | 60               | 60               |
| PARC125HD | 1 1/4" | 75               | 70               |
| PARC150HD | 1 1/2" | 80               | 82               |
| PARC200HD | 2"     | 100              | 132              |
| PARC250HD | 2 1/2" | 125              | 192              |
| PARC300HD | 3"     | 165              | 194              |
| PARC350HD | 3 1/2" | 200              | 216              |
| PARC400HD | 4"     | 330              | 232              |

#### Dimensions (in Inches):

| Cat. #    | A               | B                   |
|-----------|-----------------|---------------------|
| PARC50HD  | 5/64" - 29/64"  | 41/64" - 59/64"     |
| PARC75HD  | 3/32" - 15/32"  | 11/16" - 61/64"     |
| PARC100HD | 1/8" - 35/64"   | 23/32" - 1 7/32"    |
| PARC125HD | 5/32" - 21/32"  | 1 1/2" - 1 59/64"   |
| PARC150HD | 3/16" - 11/16"  | 1 23/32" - 2 7/8"   |
| PARC200HD | 13/64" - 37/64" | 2 17/64" - 2 39/64" |
| PARC250HD | 15/64" - 21/32" | 2 13/16" - 3 5/32"  |
| PARC300HD | 1/4" - 51/64"   | 3 25/64" - 3 59/64" |
| PARC350HD | 1/4" - 51/64"   | 3 7/8" - 4 15/32"   |
| PARC400HD | 17/64" - 13/16" | 4 9/16" - 4 55/64"  |



### EDGE TYPE CONDUIT CLAMPS – ELECTROGALVANIZED IRON

#### Applications:


- Edge type – to attach the conduit run at a 90° angle to a thin beam or structural member



| Cat. #   | Size   | Load Rating Lbs. | Unit Qty. | Wt. Lbs. Per 100 |
|----------|--------|------------------|-----------|------------------|
| ETC50HD  | 1/2"   | 30               | 50        | 63               |
| ETC75HD  | 3/4"   | 50               | 50        | 69               |
| ETC100HD | 1"     | 60               | 50        | 82               |
| ETC125HD | 1 1/4" | 75               | 25        | 95               |
| ETC150HD | 1 1/2" | 80               | 25        | 108              |
| ETC200HD | 2"     | 100              | 25        | 121              |
| ETC250HD | 2 1/2" | 125              | 25        | 153              |
| ETC300HD | 3"     | 165              | 10        | 214              |

#### Dimensions (in Inches):

| Cat. #   | A               | B        |
|----------|-----------------|----------|
| ETC50HD  | 13/64" - 11/16" | 43/64"   |
| ETC75HD  | 3/16" - 23/32"  | 1 3/64"  |
| ETC100HD | 17/64" - 47/64" | 1 9/64"  |
| ETC125HD | 9/32" - 3/4"    | 1 1/2"   |
| ETC150HD | 19/64" - 3/4"   | 1 47/64" |
| ETC200HD | 24/64" - 49/64" | 2 9/32"  |
| ETC250HD | 11/32" - 25/32" | 2 57/64" |
| ETC300HD | 3/8" - 27/32"   | 3 25/64" |



# Rigid/Intermediate Grade Conduit Fittings

## Conduit Clamps, Straps, Hangers

### J TYPE CONDUIT BEAM CLAMPS – IRON

#### Features:

JCC Series Conduit Beam Clamps are:

- Available in 1/2" to 4" sizes
- Suitable for IMC, EMT and rigid conduit
- Designed to exceed UL load requirements
- Made from ductile iron with an electrogalvanized finish
- Designed to support conduit on vertical or horizontal beams


UL File No. E-184283



| Cat. # | Size   | Jaw Opening | Unit Qty. | Load Rating Lbs. | Wt. Lbs. Per 100 |
|--------|--------|-------------|-----------|------------------|------------------|
| JCC1   | 1/2"   | 1 15/16"    | 50        | 30               | 35               |
| JCC2   | 3/4"   | 1 15/16"    | 50        | 50               | 43               |
| JCC34  | 1"     | 1 15/16"    | 75        | 75               | 90               |
|        | 1 1/4" | 1 15/16"    | 75        | 75               | 90               |
| JCC56  | 1 1/2" | 1 15/16"    | 100       | 80               | 190              |
|        | 2"     | 1 15/16"    | 100       | 100              | 190              |
| JCC78  | 2 1/2" | 1 15/16"    | 165       | 125              | 380              |
|        | 3"     | 1 15/16"    | 165       | 165              | 380              |

#### Dimensions (in Inches):

| Cat. # | A    | B    | C    |
|--------|------|------|------|
| JCC1   | 2.95 | 1.56 | 1.30 |
| JCC2   | 3.23 | 1.85 | 1.43 |
| JCC34  | 4.20 | 2.70 | 1.80 |
| JCC56  | 5.45 | 3.64 | 2.22 |
| JCC78  | 6.85 | 4.94 | 2.86 |



### HEAVY DUTY CONDUIT U-BOLTS WITH HEX NUTS – ELECTROGALVANIZED IRON



| Cat. #   | Size   | Thread Size | Unit Qty. | Wt. Lbs. Per 100 |
|----------|--------|-------------|-----------|------------------|
| UBM50HD  | 1/2"   | 5/16" - 18  | 200       | 12               |
| UBM75HD  | 3/4"   | 5/16" - 18  | 200       | 14               |
| UBM100HD | 1"     | 5/16" - 18  | 100       | 17               |
| UBM125HD | 1 1/4" | 5/16" - 18  | 50        | 19               |
| UBM150HD | 1 1/2" | 5/16" - 18  | 50        | 21               |
| UBM200HD | 2"     | 3/8" - 16   | 50        | 28               |
| UBM250HD | 2 1/2" | 3/8" - 16   | 25        | 37               |
| UBM300HD | 3"     | 3/8" - 16   | 25        | 42               |
| UBM350HD | 3 1/2" | 3/8" - 16   | 20        | 46               |
| UBM400HD | 4"     | 3/8" - 16   | 20        | 51               |