

Product Name: **O55BT**

Regulatory Information:

un 1H2/Y185/S¹
(Test report P-2237)

un 1H2/Y170/S²
(Test Report P-2226)

un 1H2/Y100/S
(Test Report P-2405)
(see note 8)

Bill of Materials:

Body:
O55BT, extrusion blow
molded high molecular
weight high density
polyethylene
(HMW-HDPE)

Cover:
Plain, one 2" opening,
or two 2" openings
available, NPS bungs,
HDPE.
Vented bungs are
available as an option.
(NPS = National Pipe
Straight thread)

Lockband:
Side lever (SLL) or bolt
ring, or plastic lockband

Product Illustration:



Nominal Capacity:

55.0 U.S. Gallons

Outage:

0.9 U.S. Gallons

Opening I.D.:

22.0 inches

Total Weight:

22.5 lbs.

Maximum Capacity:

55.9 U.S. Gallons

Outage %:

1.6 %

Nominal O.D.:

23.8 inches

Body Weight:

17.5 lbs.

Export Cubes:

11.63 cu. ft.

Overall Height:

38.8 inches

Taper Height:

31.0 inches

Nesting Height:

6.7 inches

Min. Blocking Diameter:

19.7 inches

Body Height:

38.5 inches

Min. Wall Thickness:

0.090 inches

Chime Height:

0.530 inches

Special Notes:

- 1) Maximum filling temperature 150°F. When filled at these recommended maximum filling temperatures, drums should be allowed to cool to ambient prior to stacking. Drums filled at elevated temperatures should be vented properly to prevent vacuum formation within the drum which can compromise stacking capability.
- 2) Stack 3 high (1+2) maximum with pallets between drums. Maximum top load on bottom drums not to exceed 600 lbs. each. Can be stacked (1+1) on cover without slip sheet of plywood and no additional top load. Pallets should be of good quality that provides adequate support for plastic drums.
- 3) Handle with parrotbeak, side grabber, and sling.
- 4) Drums are fully nestable without airlocking.
- 5) Recycle symbol embossed on bottom.
- 6) Patent number 5,881,898 embossed on drum.
- 7) Compatibility with hazardous materials as listed in 49CFR are the responsibility of the filler.

DISTRIBUTED BY:



REF NO.:

DWG31032

DESCRIPTION:

55 Gallon HDPE OH Drum with Cover, Nestable, UN Rated

DISCLAIMER

THIS INFORMATION IS PROVIDED AS A GENERAL GUIDE, INCLUDING DIMENSIONS. IT IS THE CUSTOMER'S RESPONSIBILITIES TO SELECT THE PROPER CONTAINER FOR PRODUCT AND APPLICATION COMPATIBILITY.