



FINISHES: MATTE

| | | | |
|---------------------|------------------------|-----------------------|--------------------------------|
| <p>USAGE</p> | <p>MATERIAL</p> | <p>PRICING</p> | <p>SPECIAL FEATURES</p> |
|---------------------|------------------------|-----------------------|--------------------------------|

STONE LOOK

GLAZED PORCELAIN FLOOR TILE WITH STEPWISE™ TECHNOLOGY



COOL BEIGE ME07



LIGHT GRAY ME08



DARK GRAY ME09


GLAZED PORCELAIN MOSAIC WITH STEPWISE™ TECHNOLOGY



COOL BEIGE ME07



LIGHT GRAY ME08



DARK GRAY ME09



50% MORE
SLIP RESISTANT
THAN ORDINARY TILE*



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT
*Not Applicable to Mesh-Mounted Mosaics



INDOOR/OUTDOOR



SIMPLICLEAN™

VISIT AMERICANOLEAN.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE

USAGE




MATERIAL



PRICING



SPECIAL FEATURES



STONE LOOK

SIZES

| | | | THICKNESS | SQ. FT./ CARTON | PIECES/ CARTON |
|--|-----------------------------------|--|-----------|--------------------|-------------------|
| | 12 x 24 Floor Tile | 11-13/16" x 11-13/16" (30.00 cm x 30.00 cm) | 3/8" | 15.60 | 8 |
| | 2 x 2 Mosaic (Mesh-Mounted) | 12" x 12" Sheet (30.48 cm x 30.48 cm Sheet) | 3/8" | 10.00 | 10 |

INSTALLATION & PRICING

| Grout Joint Recommendation | Shade Variation |
|---|-----------------------------|
| <p>Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)</p> <p>Mosaic: 1/8"</p> | <p>HIGH (V3)</p> |

PERFORMANCE CHARACTERISTICS

| | ASTM# | FLOOR RESULT | MOSAIC RESULT |
|---------------------|-------|-----------------|------------------|
| Water Absorption | C373 | < 0.5% | < 0.5% |
| Breaking Strength | C648 | > 275 lbs. | > 275 lbs. |
| Scratch Hardness | MOHS | 8.0 | 8.0 |
| Chemical Resistance | C650 | Resistant | Resistant |

For additional information on test results, visit us at: americanolean.com/information/TestResults.

DURABILITY

| Floor Surface Wear Resistance | | |
|-------------------------------|-----------------------|--------------------------------------|
| 1 | Residential Bathrooms | 3 All Residential / Light Commercial |
| 2 | All Residential Areas | ④ All Residential / Commercial |

FEATURES



All or select items within this series meet the requirements for these qualifications. For more information visit americanolean.com.

TRIM

| | | | NUMBER | PIECES/ CARTON |
|--|----------------|--------|--------|-------------------|
| | Floor Bullnose | 3 x 12 | P43C9 | 30 |

Floor bullnose trim is intended to coordinate with floor tile in the standard 90-degree installation position.

APPLICATIONS

| | TARGET DCOF WET | SUITABLE |
|---|--------------------|----------|
| Dry & Level – Interior Floor | N/A | ● |
| Wet & Level – Interior Floor | ≥ 0.42 | ● |
| Shower Floors (Residential or Light Commercial) | ≥ 0.42 | ●* |
| Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear) | ≥ 0.60 | ● |
| Ramps & Inclines | ≥ 0.65 | |
| Walls/Backsplashes | N/A | ● |
| Countertops | N/A | ● |
| Pool Linings | N/A | ●* |

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit americanolean.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

* Mosaic tile only.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: americanolean.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to americanolean.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit americanolean.com.