SONANCE

DATA SHEET

R1SUR | R2SUR REFERENCE IN-WALL SURROUND SPEAKER

TECHNICAL SPECIFICATIONS

 R1SUR

 SKU
 93345

 UOM
 Each

Tweeter Two 1" (25mm) Ceramic domes,

Ferrofluid-cooled

Midrange Two 3" (76mm) Carbon fiber/Rohacell

laminated cones with rubber surrounds

Woofer Two 5 1/4" (133mm) Carbon fiber/Rohacell

laminated cones with rubber surrounds

Frequency Response 70Hz - 30Hz +/-3dB

Impedance 8 ohms nominal; 6 ohms minimum

Power Handling 5 Watts minimum; 150 Watts maximum

Sensitivity 90dB SPL (2.83V/1 meter)

 Dimensions
 8.875" x 21.75" x 3.875"

 (WxHxD)
 (225mm x 553mm x 98mm)

Cut-Out Dimensions 7.5" x 20.5"

(WxH) $(191mm \times 521mm)$

Shipping Weight 19 lbs (8.6 kg)

R2SUR 93347

Each

Two 1" (25mm) Ceramic domes,

Ferrofluid-cooled

Two 3" (76mm) Carbon fiber/Rohacell laminated cones with rubber surrounds

Four 5 1/4" (133mm) Carbon fiber/Rohacell laminated cones with rubber surrounds

animated cories with rubber surrour

70Hz - 30Hz +/-3dB

6 ohms nominal; 4 ohms minimum

5 Watts minimum; 200 Watts maximum

92dB SPL (2.83V/1 meter)


8.875" x 34.875" x 3.875" (225mm x 886mm x 98mm)

7.5" x 33.5"

(191mm x 851mm)


29 lbs (13.2 kg)

DIMENSIONAL DRAWINGS



Front View

3.875" (98mm) **Side View**



Front View

3.875" (98mm)

Side View

ASSOCIATED PRODUCTS

R1 | R1SUR Flex Bracket (Each) 92690 R2 | R2SUR Flex Bracket (Each) 92691

LIMITED FIVE (5) YEAR WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.

©2025 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.