

Ductless Mini and Multi-Split Quick Reference Guide



 **Tempo**
SERIES

 **FlexFit**
SERIES

 **Arctic**
SERIES



GE APPLIANCES
a Haier company


AIR&WATER
SOLUTIONS

Single-Zone Systems



- Up to 23 SEER2; 9.5 HSPF2
- 09/12K 115V options with basepan heater
- 09/12/18/24K 230V options with highwall matches

OPERATING RANGE (°F):



Standard Highwall




	Size	Outdoor Model	Indoor Model	AHRI#	Max Heat @ 5°F	SEER2/ EER2/ HSPF2 (IV)	Lineset: Liquid Suction	Min/ Max Line Length	Rec. Breaker Size A	Min Circuit Amp
115V	9K	1Q09TE1BEA	QS09WB1BEA	215564827	7,000	20/12/9.5	1/4" - 3/8"	10'/66'	20	18
	12K	1Q12TE1BEA	QS12WB1BEA	215564828	9,000	20/12/9.5	1/4" - 3/8"	10'/66'	20	18
	9K	1Q09TE2BEA	QS09WB2BEA	217124721	8,000	23/12/9.5	1/4" - 3/8"	10'/66'	15	9
	12K	1Q12TE2BEA	QS12WB2BEA	217124722	10,400	21/12/9.5	1/4" - 3/8"	10'/66'	15	9
	18K	1Q18TE2BEA	QS18WB2BEA	217124723	15,200	20/12/9.5	1/4" - 1/2"	10'/83'	15	15
	24K	1Q24TE2BEA	QS24WB2BEA	217124724	19,200	18/12/9.5	1/4" - 1/2"	10'/165'	20	20

Quick Reference Guide

Single-Zone Systems



- Up to 23 SEER2; 9.5 HSPF2
- Low ambient heating down to -15°F (built-in basepan heater)
- -40°F low ambient cooling with wind baffle & top cover (sold separately)



Standard Highwall



Size	Outdoor Model	Indoor Model	AHRI#	Max Heat @ 5°F	SEER2/EER2/HSPF2 (IV)	Lineset: Liquid Suction	Min/Max Line Length	Rec. Breaker Size A	Min Circuit Amp
9K	1Q09FF2BEA	QS09WB2BEA	216968341	8,000	23/12/9.5	1/4" - 3/8"	10'/66'	15	9
12K	1Q12FF2BEA	QS12WB2BEA	216968342	10,400	21/12/9.5	1/4" - 3/8"	10'/66'	15	9
15K	1Q15FF2BEA	QS15WB2BEA	216968343	13,600	21/11.7/9.5	1/4" - 3/8"	10'/66'	15	14
18K	1Q18FF2BEA	QS18WB2BEA	216968344	15,200	20/12/9.5	1/4" - 1/2"	10'/83'	15	15
24K	1Q24FF2BEA	QS24WB2BEA	216968345	19,200	18/12/9.5	1/4" - 1/2"	10'/165'	20	20
30K	1Q3036FF2BEA	QS30WB2BEA	216968346	26,000	18/12/9.5	3/8" - 5/8"	10'/165'	30	25
36K	1Q3036FF2BEA	QS36WB2BEA	216968347	24,000	18/9.8/9.5	3/8" - 5/8"	10'/165'	30	25

Cassette



Size	Outdoor Model	Indoor Model	AHRI#	Max Heat @ 5°F	SEER2/EER2/HSPF2 (IV)	Lineset: Liquid Suction	Min/Max Line Length	Rec. Breaker Size A	Min Circuit Amp
ONE-WAY	9K	1Q09FF2BEA	US09AB2BEA*	9,000	23/14/10.6	1/4" - 3/8"	10'/66'	15	9
	12K	1Q12FF2BEA	US12AB2BEA*	10,500	23/12.4/10.2	1/4" - 3/8"	10'/66'	15	9
	18K	1Q18FF2BEA	US18AB2BEA*	15,000	19/11.2/9.5	1/4" - 1/2"	10'/83'	15	15
4-WAY COMPACT	9K	1Q09FF2BEA	US09CB2BEA**	7,500	20/12.2/9.5	1/4" - 3/8"	10'/66'	15	9
	12K	1Q12FF2BEA	US12CB2BEA**	9,000	19.8/12/9.5	1/4" - 3/8"	10'/66'	15	9
	18K	1Q18FF2BEA	US18CB2BEA**	14,400	18.5/11.7/9.1	1/4" - 1/2"	10'/83'	15	15
4-WAY LARGE	24K	1Q24FF2BEA	US24LB2BEA***	20,000	19.5/11.7/9.5	3/8" - 5/8"	10'/165'	20	20
	30K	1Q3036FF2BEA	US30LB2BEA***	24,000	19/11.2/10	3/8" - 3/4"	10'/165'	30	25
	36K	1Q3036FF2BEA	US36LB2BEA***	26,000	18.8/10.6/9.3	3/8" - 3/4"	10'/165'	30	25


Built-In condensate pump.

*QAABP0718A panel required (sold separately).

**QACCP01WA panel required (sold separately).

***QALCP01WA panel required (sold separately).

Console



Size	Outdoor Model	Indoor Model	AHRI#	Max Heat @ 5°F	SEER2/EER2/HSPF2 (IV)	Lineset: Liquid Suction	Min/Max Line Length	Rec. Breaker Size A	Min Circuit Amp
9K	1Q09FF2BEA	US09FB2BEA	217456248	8,500	20/12/9.5	1/4" - 3/8"	10'/66'	15	9
12K	1Q12FF2BEA	US12FB2BEA	217456249	9,500	19/9.5/9.2	1/4" - 3/8"	10'/66'	15	9
18K	1Q18FF2BEA	US18FB2BEA	217456250	12,600	17/8.6/7.8	1/4" - 1/2"	10'/83'	15	15

Mid-Static Ducted



Size	Outdoor Model	Indoor Model	AHRI#	Max Heat @ 5°F	SEER2/EER2/HSPF2 (IV)	Lineset: Liquid Suction	Min/Max Line Length	Rec. Breaker Size A	Min Circuit Amp
9K	1Q09FF2BEA	US09MB2BEA	217456254	8,000	17.8/11.7/9.4	1/4" - 3/8"	10'/66'	15	9
12K	1Q12FF2BEA	US12MB2BEA	217456255	9,100	17/10.3/9.4	1/4" - 3/8"	10'/66'	15	9
18K	1Q18FF2BEA	US18MB2BEA	217456256	15,200	17.3/10.8/9	1/4" - 1/2"	10'/83'	15	15
24K	1Q24FF2BEA	US24MB2BEA	217456257	20,000	18/10/9.4	3/8" - 5/8"	10'/165'	20	20
30K	1Q3036FF2BEA	US30MB2BEA	217456258	25,000	17/10.3/9.4	3/8" - 3/4"	10'/165'	30	25
36K	1Q3036FF2BEA	US36MB2BEA	217456259	25,200	16/9.5/9	3/8" - 3/4"	10'/165'	30	25


Built-In condensate pump.

Quick Reference Guide

Single-Zone Systems



- Up to 27 SEER2; 11 HSPF2
- Cold climate compressor with basepan heater allows low ambient heating down to -31°F
- Warm air in extreme conditions; up to 100% rated heating capacity at 5°F
- Premium highwall includes built-in smart sensor



Premium Highwall



Size	Outdoor Model	Indoor Model	AHRI#	Max Heat @ 5°F	SEER2/EER2/HSPF2 (IV)	Lineset: Liquid Suction	Min/Max Line Length	Rec. Breaker Size A	Min Circuit Amp
9K	1Q09RT2BEA	QS09WP2BEA QS09WP2BEB*	215876548	10,000	27/12.5/11	1/4" - 3/8"	10'/66'	15	13
12K	1Q12RT2BEA	QS12WP2BEA QS12WP2BEB*	215876549	14,500	25/12.5/11	1/4" - 3/8"	10'/66'	15	14
18K	1Q18RT2BEA	QS18WP2BEA QS18WP2BEB*	215876550	19,000	20.5/12/10	1/4" - 1/2"	10'/83'	20	20
24K	1Q24RT2BEA	QS24WP2BEA QS24WP2BEB*	217465732	22,000	20/11.2/9.5	1/4" - 1/2"	10'/165'	25	22


* With built-In Refrigerant Detection Sensor (RDS)

Standard Highwall



Size	Outdoor Model	Indoor Model	AHRI#	Max Heat @ 5°F	SEER2/EER2/HSPF2 (IV)	Lineset: Liquid Suction	Min/Max Line Length	Rec. Breaker Size A	Min Circuit Amp
30K	1Q3036RT2BEA	QS30WB2BEA	217465734	25,800	20/11.2/9.5	3/8" - 5/8"	10'/165'	30	25
36K	1Q3036RT2BEA	QS36WB2BEA	217465736	26,200	20/10.5/9.5	3/8" - 5/8"	10'/165'	30	25

Cassette



Size	Outdoor Model	Indoor Model	AHRI#	Max Heat @ 5°F	SEER2/EER2/HSPF2 (IV)	Lineset: Liquid Suction	Min/Max Line Length	Rec. Breaker Size A	Min Circuit Amp
ONE-WAY	9K	1Q09RT2BEA	US09AB2BEA*	11,000	25/14.6/12	1/4" - 3/8"	10'/66'	15	13
	12K	1Q12RT2BEA	US12AB2BEA*	12,600	24.5/14/10	1/4" - 3/8"	10'/66'	15	14
	18K	1Q18RT2BEA	US18AB2BEA*	18,000	21/12/10.2	1/4" - 1/2"	10'/83'	20	20
4-WAY COMPACT	9K	1Q09RT2BEA	US09CB2BEA**	9,000	20/12/10	1/4" - 3/8"	10'/66'	15	13
	12K	1Q12RT2BEA	US12CB2BEA**	10,000	20/12/10	1/4" - 3/8"	10'/66'	15	14
	18K	1Q18RT2BEA	US18CB2BEA**	14,400	20/12/10	1/4" - 1/2"	10'/83'	20	20
4-WAY LARGE	24K	1Q24RT2BEA	US24LB2BEA***	22,000	20/12/10	3/8" - 5/8"	10'/165'	25	22
	30K	1Q3036RT2BEA	US30LB2BEA***	27,000	20/12/10	3/8" - 3/4"	10'/165'	25	25
	36K	1Q3036RT2BAA	US36LB2BEA***	29,000	19/11/10	3/8" - 3/4"	10'/165'	30	25

Built-In condensate pump.

*QAABP0718A panel required (sold separately).

**QACCP01WA panel required (sold separately).

***QALCP01WA panel required (sold separately).

Console



Size	Outdoor Model	Indoor Model	AHRI#	Max Heat @ 5°F	SEER2/EER2/HSPF2 (IV)	Lineset: Liquid Suction	Min/Max Line Length	Rec. Breaker Size A	Min Circuit Amp
9K	1Q09RT2BEA	US09FB2BEA	217036485	9,000	20/12/10.5	1/4" - 3/8"	10'/66'	15	13
12K	1Q12RT2BEA	US12FB2BEA	217036486	10,000	20/12/9.5	1/4" - 3/8"	10'/66'	15	14
18K	1Q18RT2BEA	US18FB2BEA	217036487	14,400	19/9/9.5	1/4" - 1/2"	10'/83'	20	20

Mid-Static Ducted



Size	Outdoor Model	Indoor Model	AHRI#	Max Heat @ 5°F	SEER2/EER2/HSPF2 (IV)	Lineset: Liquid Suction	Min/Max Line Length	Rec. Breaker Size A	Min Circuit Amp
9K	1Q09RT2BEA	US09MB2BEA	217036491	8,000	19.6/12/10.5	1/4" - 3/8"	10'/66'	15	13
12K	1Q12RT2BEA	US12MB2BEA	217036492	10,000	19.8/11.7/10.5	1/4" - 3/8"	10'/66'	15	14
18K	1Q18RT2BEA	US18MB2BEA	217036493	17,000	18/11.7/10.5	1/4" - 1/2"	10'/83'	20	20
24K	1Q24RT2BEA	US24MB2BEA	217456220	23,000	18.2/11.7/10.5	3/8" - 5/8"	10'/165'	25	22
30K	1Q3036RT2BEA	US30MB2BEA	217456221	24,000	17.6/10.8/10	3/8" - 3/4"	10'/165'	30	25
36K	1Q3036RT2BEA	US36MB2BEA	217456222	26,000	17.4/9.8/9.5	3/8" - 3/4"	10'/165'	30	25

Built-In condensate pump.


Quick Reference Guide

Multi-Zone Systems

Multi-Zone Outdoor Units




OPERATING RANGE (°F):




- Up to 24 SEER2; 10.0 HSPF2
- Provides ~ 65% heating capacity at 5°F

Size	Outdoor Model	Max Line All Comb.	Max Heat @ 5°F Non-Ducted	SEER2/EER2/HSPF2 (IV) Non-Ducted	SEER2/EER2/HSPF2 (IV) Ducted	AHRI#		Rec. Breaker Size A	Min Circuit Amp
						Non-Ducted	Ducted		
18K	2Q18FF2BEA	98'	16,600	22.5/12/10.5	18.8/10.8/9.5	217009754	217021962	25	16
24K	3Q24FF2BEA	197'	17,600	24/12/10.2	17.2/10.5/9.5	217009755	217021963	25	18
36K	4Q36FF2BEA	230'	23,000	20/10/10	16.5/8.8/9.3	217009760	217021964	30	22



OPERATING RANGE (°F):



- Up to 23 SEER2; 10.5 HSPF2
- Built-In basepan heater allows operating down to -22°F
- Provides ~ 90% heating capacity at 5°F

Size	Outdoor Model	Max Line All Comb.	Max Heat @ 5°F Non-Ducted	SEER2/EER2/HSPF2 (IV) Non-Ducted	SEER2/EER2/HSPF2 (IV) Ducted	AHRI#		Rec. Breaker Size A	Min Circuit Amp
						Non-Ducted	Ducted		
20K	2Q20RT2BEA	164'	20,000	20.6/12.3/10.5	17.6/10.8/10.5	217009756	217021965	30	20
24K	3Q24RT2BEA	197'	22,800	23/12.2/10.5	17.2/10.5/10	217009757	217021966	30	21
36K	4Q36RT2BEA	230'	34,000	20.5/11/10	17.4/10.2/10	217009758	217021967	40	35
42K	5Q42RT2BEA	262'	35,000	20.5/10.5/9.5	17.4/10.2/9.5	217009759	217021968	40	36

Multi-Zone Indoor Units



Highwall

Size	Indoor Model	Lineset: Liquid Suction
------	--------------	-------------------------

Standard

7K	QS07WB2BEA	1/4" - 3/8"
9K	QS09WB2BEA	1/4" - 3/8"
12K	QS12WB2BEA	1/4" - 3/8"
15K	QS15WB2BEA	1/4" - 3/8"
18K	QS18WB2BEA	1/4" - 1/2"
24K	QS24WB2BEA	1/4" - 1/2"

Premium

6K	QS06WP2BEA*	1/4" - 3/8"
9K	QS09WP2BEA	1/4" - 3/8"
	QS09WP2BEB*	1/4" - 3/8"
12K	QS12WP2BEA	1/4" - 3/8"
	QS12WP2BEB*	1/4" - 3/8"
18K	QS18WP2BEA	1/4" - 1/2"
	QS18WP2BEB*	1/4" - 1/2"
24K	QS24WP2BEA	1/4" - 1/2"
	QS24WP2BEB*	1/4" - 1/2"

* With built-In Refrigerant Detection Sensor (RDS)



Cassette

Size	Indoor Model	Lineset: Liquid Suction
------	--------------	-------------------------

One-Way

7K	US07AB2BEA ¹	1/4" - 3/8"
9K	US09AB2BEA ¹	1/4" - 3/8"
12K	US12AB2BEA ¹	1/4" - 3/8"
18K	US18AB2BEA ¹	1/4" - 1/2"

4-Way

9K	US09CB2BEA ²	1/4" - 3/8"
12K	US12CB2BEA ²	1/4" - 3/8"
18K	US18CB2BEA ²	1/4" - 1/2"
24K	US24LB2BEA ³	3/8" - 5/8"

Built-In condensate pump.

¹QAABP0718A panel required (sold separately).

²QACCP01WA panel required (sold separately).

³QALCP01WA panel required (sold separately).

Console

Size	Indoor Model	Lineset: Liquid Suction
------	--------------	-------------------------

9K	US09FB2BEA	1/4" - 3/8"
12K	US12FB2BEA	1/4" - 3/8"
18K	US18FB2BEA	1/4" - 1/2"



Mid-Static Ducted

Size	Indoor Model	Lineset: Liquid Suction
------	--------------	-------------------------

7K	US07MB2BEA	1/4" - 3/8"
9K	US09MB2BEA	1/4" - 3/8"
12K	US12MB2BEA	1/4" - 3/8"
18K	US18MB2BEA	1/4" - 1/2"
24K	US24MB2BEA	3/8" - 5/8"

Built-In condensate pump.

Multi-Zone Capacity Combination Matrix

Piping Adapter Guide

■ 6-15K MODELS

- These units use 1/4" liquid and 3/8" vapor lines.
- Check the multi-zone unit for a port that matches these sizes.
- If an adapter is required, install on the outdoor unit port side.

ODU Port Size	Adapter	Description	Part Number
1/4" & 3/8"	None	Direct Connection	-
1/4" & 1/2"	E	1/2" to 3/8" (vapor line)	WJ01X26854

■ ALL 18K MODELS & 24K HIGHWALL MODELS (QS24WB2BE**/QS24WP2BE**)

- These units use 1/4" liquid and 1/2" vapor lines.
- Check the multi-zone unit for a port that matches these sizes.
- If an adapter is required, install on the outdoor unit port side.

ODU Port Size	Adapter	Description	Part Number
1/4" & 1/2"	None	Direct Connection	-
1/4" & 3/8"	D	3/8" to 1/2" (vapor line)	WJ01X26853

■ 24K CASSETTE/DUCTED

(US24LB2BE**/US24MB2BE**)

- These units use 3/8" liquid and 5/8" vapor lines.
- No multi-zone ports match these sizes directly.
- Adapters are required - install on the outdoor unit port side.

ODU Port Size	Adapter	Description	Part Number
1/4" & 3/8"	A	1/4" to 3/8" (liquid line)	WJ01X23925
	B	3/8" to 5/8" (vapor line)	WJ01X23924
1/4" & 1/2"	A	1/4" to 3/8" (liquid line)	WJ01X23925
	C	1/2" to 5/8" (vapor line)	WJ01X23932

QUICK TIPS

- Always check port sizes first before installing.
- Use adapters only on the outdoor unit side.
- Label adapters if needed to avoid confusion during service.
- Keep common adapters in your kit for faster installs.



2Q18FF2BE**

2Q20RT2BE**

- No adapters required
- Port Sizes:
 - » Port B: 1/4" x 3/8"
 - » Port A: 1/4" x 3/8"

Combinations

		Ports					
		B	A	B	A	B	A
Two-Zone	9K	9K	9K	9K	15K	6K	
	12K	6K	12K	6K	15K	7K	
	12K	7K	12K	7K	15K	9K	
	12K	9K	12K	9K			
	12K	12K	12K	12K			



3Q24FF2BE**


3Q24RT2BE**

- Ships with adapter D
- No adapters required for Ports B, A
- Port Sizes:
 - » Port C: 1/4" x 3/8"
 - » Port B: 1/4" x 3/8"
 - » Port A: 1/4" x 3/8"

Combinations

		Ports											
		C	B	A	C	B	A	C	B	A	C	B	A
Two-Zone	6K	6K	-	12K	6K	-	15K	9K	-	18K	12K	-	
	7K	6K	-	12K	7K	-	15K	12K	-	24K	6K	-	
	7K	7K	-	12K	9K	-	15K	15K	-	24K	7K	-	
	9K	6K	-	12K	12K	-	18K	6K	-	24K	9K	-	
	9K	7K	-	15K	6K	-	18K	7K	-				
	9K	9K	-	15K	7K	-	18K	9K	-				
Three-Zone	6K	6K	6K	9K	9K	6K	12K	9K	7K	15K	7K	7K	
	7K	6K	6K	9K	9K	7K	12K	9K	9K	15K	9K	6K	
	7K	7K	6K	9K	9K	9K	12K	12K	6K	15K	9K	7K	
	7K	7K	7K	12K	6K	6K	12K	12K	7K	15K	9K	9K	
	9K	6K	6K	12K	7K	6K	12K	12K	9K	18K	6K	6K	
	9K	7K	6K	12K	7K	7K	15K	6K	6K	18K	7K	6K	
	9K	7K	7K	12K	9K	6K	15K	7K	6K	18K	7K	7K	

Multi-Zone Capacity Combination Matrix




4Q36FF2BE** 4Q36RT2BE**

- Ships with adapters D and E
- No adapters required for Ports B, A
- Port Sizes:
 - » Port D: 1/4" x 1/2"
 - » Port C: 1/4" x 3/8"
 - » Port B: 1/4" x 3/8"
 - » Port A: 1/4" x 3/8"

Combinations

		Ports															
		D	C	B	A	D	C	B	A	D	C	B	A	D	C	B	A
Two-Zone		18K	9K	-	-	18K	18K	-	-	24K	7K	-	-	24K	15K	-	-
		18K	12K	-	-	18K	24K	-	-	24K	9K	-	-	24K	24K	-	-
		18K	15K	-	-	24K	6K	-	-	24K	12K	-	-				
Three-Zone		-	9K	9K	9K	-	15K	12K	6K	18K	9K	9K	-	24K	6K	6K	-
		-	12K	9K	6K	-	15K	12K	7K	18K	12K	6K	-	24K	7K	6K	-
		-	12K	9K	7K	-	15K	12K	9K	18K	12K	7K	-	24K	7K	7K	-
		-	12K	9K	9K	-	15K	12K	12K	18K	12K	9K	-	24K	9K	6K	-
		-	12K	12K	6K	-	15K	15K	6K	18K	12K	12K	-	24K	9K	7K	-
		-	12K	12K	7K	-	15K	15K	7K	18K	15K	6K	-	24K	9K	9K	-
		-	12K	12K	9K	-	15K	15K	9K	18K	15K	7K	-	24K	12K	6K	-
		-	12K	12K	12K	-	15K	15K	12K	18K	15K	9K	-	24K	12K	7K	-
		-	15K	6K	6K	-	15K	15K	15K	18K	15K	12K	-	24K	12K	9K	-
		-	15K	7K	6K	18K	6K	6K	-	18K	15K	15K	-	24K	12K	12K	-
		-	15K	7K	7K	18K	7K	6K	-	18K	18K	6K	-	24K	15K	6K	-
		-	15K	9K	6K	18K	7K	7K	-	18K	18K	7K	-	24K	15K	7K	-
		-	15K	9K	7K	18K	9K	6K	-	18K	18K	9K	-	24K	15K	9K	-
		-	15K	9K	9K	18K	9K	7K	-	18K	18K	12K	-				
Four-Zone		6K	6K	6K	6K	12K	9K	9K	6K	15K	9K	9K	9K	18K	9K	7K	6K
		7K	6K	6K	6K	12K	9K	9K	7K	15K	12K	6K	6K	18K	9K	7K	7K
		7K	7K	6K	6K	12K	9K	9K	9K	15K	12K	7K	6K	18K	9K	9K	6K
		7K	7K	7K	6K	12K	12K	6K	6K	15K	12K	7K	7K	18K	9K	9K	7K
		7K	7K	7K	7K	12K	12K	7K	6K	15K	12K	9K	6K	18K	9K	9K	9K
		9K	6K	6K	6K	12K	12K	7K	7K	15K	12K	9K	7K	18K	12K	6K	6K
		9K	7K	6K	6K	12K	12K	9K	6K	15K	12K	9K	9K	18K	12K	7K	6K
		9K	7K	7K	6K	12K	12K	9K	7K	15K	12K	12K	6K	18K	12K	7K	7K
		9K	7K	7K	7K	12K	12K	9K	9K	15K	12K	12K	7K	18K	12K	9K	6K
		9K	9K	6K	6K	12K	12K	12K	6K	15K	12K	12K	9K	18K	12K	9K	7K
		9K	9K	7K	6K	12K	12K	12K	7K	15K	12K	12K	12K	18K	12K	9K	9K
		9K	9K	7K	7K	12K	12K	12K	9K	15K	15K	6K	6K	18K	15K	6K	6K
		9K	9K	9K	6K	12K	12K	12K	12K	15K	15K	7K	6K	18K	15K	7K	6K
		9K	9K	9K	7K	15K	6K	6K	6K	15K	15K	7K	7K	18K	15K	7K	7K
		9K	9K	9K	9K	15K	7K	6K	6K	15K	15K	9K	6K	18K	15K	9K	6K
		12K	6K	6K	6K	15K	7K	7K	6K	15K	15K	9K	7K	24K	6K	6K	6K
		12K	7K	6K	6K	15K	7K	7K	7K	15K	15K	9K	9K	24K	7K	6K	6K
		12K	7K	7K	6K	15K	9K	6K	6K	18K	6K	6K	6K	24K	7K	7K	6K
		12K	7K	7K	7K	15K	9K	7K	6K	18K	7K	6K	6K	24K	7K	7K	7K
		12K	9K	6K	6K	15K	9K	7K	7K	18K	7K	7K	6K	24K	9K	6K	6K
		12K	9K	7K	6K	15K	9K	9K	6K	18K	7K	7K	7K	24K	9K	7K	6K
		12K	9K	7K	7K	15K	9K	9K	7K	18K	9K	6K	6K	24K	9K	7K	7K

Multi-Zone Capacity Combination Matrix



5Q42RT2BE**

- Ships with (2) adapter E
- No adapters required for Ports B, A
- Port Sizes:
 - » Port E: 1/4" x 1/2"
 - » Port D: 1/4" x 1/2"
 - » Port C: 1/4" x 3/8"
 - » Port B: 1/4" x 3/8"
 - » Port A: 1/4" x 3/8"

See
Piping Adapter Guide
On Previous Page

Combinations

	Ports																			
	E	D	C	B	A	E	D	C	B	A	E	D	C	B	A	E	D	C	B	A
Two-Zone	18K	-	9K	-	-	18K	18K	-	-	-	24K	-	9K	-	-	24K	18K	-	-	-
	18K	-	12K	-	-	24K	-	6K	-	-	24K	-	12K	-	-	24K	24K	-	-	-
	18K	-	15K	-	-	24K	-	7K	-	-	24K	-	15K	-	-					
Three-Zone	-	-	9K	9K	9K	-	-	15K	12K	9K	18K	-	12K	12K	-	24K	-	9K	7K	-
	-	-	12K	9K	6K	-	-	15K	12K	12K	18K	-	15K	6K	-	24K	-	9K	9K	-
	-	-	12K	9K	7K	-	-	15K	15K	6K	18K	-	15K	7K	-	24K	-	12K	6K	-
	-	-	12K	9K	9K	-	-	15K	15K	7K	18K	-	15K	9K	-	24K	-	12K	7K	-
	-	-	12K	12K	6K	-	-	15K	15K	9K	18K	-	15K	12K	-	24K	-	12K	9K	-
	-	-	12K	12K	7K	-	-	15K	15K	12K	18K	-	15K	15K	-	24K	-	12K	12K	-
	-	-	12K	12K	9K	-	-	15K	15K	15K	18K	18K	6K	-	-	24K	-	15K	6K	-
	-	-	12K	12K	12K	18K	-	6K	6K	-	18K	18K	7K	-	-	24K	-	15K	7K	-
	-	-	15K	6K	6K	18K	-	7K	6K	-	18K	18K	9K	-	-	24K	-	15K	9K	-
	-	-	15K	7K	6K	18K	-	7K	7K	-	18K	18K	12K	-	-	24K	-	15K	12K	-
	-	-	15K	7K	7K	18K	-	9K	6K	-	18K	18K	15K	-	-	24K	-	15K	15K	-
	-	-	15K	9K	6K	18K	-	9K	7K	-	18K	18K	18K	-	-	24K	18K	6K	-	-
	-	-	15K	9K	7K	18K	-	9K	9K	-	24K	-	6K	6K	-	24K	18K	7K	-	-
	-	-	15K	9K	9K	18K	-	12K	6K	-	24K	-	7K	6K	-	24K	18K	9K	-	-
	-	-	15K	12K	6K	18K	-	12K	7K	-	24K	-	7K	7K	-	24K	18K	12K	-	-
	-	-	15K	12K	7K	18K	-	12K	9K	-	24K	-	9K	6K	-	24K	18K	15K	-	-
Four-Zone	6K	-	6K	6K	6K	12K	-	12K	12K	9K	18K	-	7K	6K	6K	18K	18K	9K	6K	-
	7K	-	6K	6K	6K	12K	-	12K	12K	12K	18K	-	7K	7K	6K	18K	18K	9K	7K	-
	7K	-	7K	6K	6K	15K	-	6K	6K	6K	18K	-	7K	7K	7K	18K	18K	9K	9K	-
	7K	-	7K	7K	7K	15K	-	7K	6K	6K	18K	-	9K	6K	6K	18K	18K	12K	6K	-
	9K	-	6K	6K	6K	15K	-	7K	7K	6K	18K	-	9K	7K	6K	18K	18K	12K	7K	-
	9K	-	7K	6K	6K	15K	-	7K	7K	7K	18K	-	9K	7K	7K	18K	18K	12K	9K	-
	9K	-	7K	7K	6K	15K	-	9K	6K	6K	18K	-	9K	9K	6K	24K	-	6K	6K	6K
	9K	-	7K	7K	7K	15K	-	9K	7K	6K	18K	-	9K	9K	7K	24K	-	7K	6K	6K
	9K	-	9K	6K	6K	15K	-	9K	7K	7K	18K	-	9K	9K	9K	24K	-	7K	7K	6K
	9K	-	9K	7K	6K	15K	-	9K	9K	6K	18K	-	12K	6K	6K	24K	-	7K	7K	7K
	9K	-	9K	7K	7K	15K	-	9K	9K	7K	18K	-	12K	7K	6K	24K	-	9K	6K	6K
	9K	-	9K	9K	6K	15K	-	9K	9K	9K	18K	-	12K	7K	7K	24K	-	9K	7K	6K
	9K	-	9K	9K	7K	15K	-	12K	6K	6K	18K	-	12K	9K	6K	24K	-	9K	7K	7K
	9K	-	9K	9K	9K	15K	-	12K	7K	6K	18K	-	12K	9K	7K	24K	-	9K	9K	6K
	12K	-	6K	6K	6K	15K	-	12K	7K	7K	18K	-	12K	9K	9K	24K	-	9K	9K	7K
	12K	-	7K	6K	6K	15K	-	12K	9K	6K	18K	-	12K	12K	6K	24K	-	9K	9K	9K
	12K	-	7K	7K	6K	15K	-	12K	9K	7K	18K	-	12K	12K	7K	24K	-	12K	6K	6K
	12K	-	7K	7K	7K	15K	-	12K	9K	9K	18K	-	12K	12K	9K	24K	-	12K	7K	6K
	12K	-	9K	6K	6K	15K	-	12K	12K	6K	18K	-	12K	12K	12K	24K	-	12K	7K	7K
	12K	-	9K	7K	6K	15K	-	12K	12K	7K	18K	-	15K	6K	6K	24K	-	12K	9K	6K
	12K	-	9K	7K	7K	15K	-	12K	12K	9K	18K	-	15K	7K	6K	24K	-	12K	9K	7K
	12K	-	9K	9K	6K	15K	-	12K	12K	12K	18K	-	15K	7K	7K	24K	-	12K	9K	9K
	12K	-	9K	9K	7K	15K	-	15K	6K	6K	18K	-	15K	9K	6K	24K	-	12K	12K	6K
	12K	-	9K	9K	9K	15K	-	15K	7K	6K	18K	-	15K	9K	7K	24K	-	12K	12K	7K
	12K	-	12K	6K	6K	15K	-	15K	7K	7K	18K	-	15K	9K	9K	24K	-	15K	6K	6K
	12K	-	12K	7K	6K	15K	-	15K	9K	6K	18K	-	15K	12K	6K	24K	-	15K	7K	6K
	12K	-	12K	7K	7K	15K	-	15K	9K	7K	18K	-	15K	12K	7K	24K	-	15K	7K	7K
	12K	-	12K	9K	6K	15K	-	15K	9K	9K	18K	-	15K	12K	9K	24K	-	15K	9K	6K
	12K	-	12K	9K	7K	15K	-	15K	12K	9K	18K	-	15K	12K	12K	24K	-	15K	9K	7K
	12K	-	12K	9K	9K	15K	-	15K	12K	12K	18K	18K	6K	6K	-	24K	18K	6K	6K	-
	12K	-	12K	12K	6K	15K	-	15K	15K	12K	18K	18K	7K	6K	-	24K	18K	7K	6K	-
	12K	-	12K	12K	7K	18K	-	6K	6K	6K	18K	18K	7K	7K	-	24K	18K	7K	7K	-

Multi-Zone Capacity Combination Matrix

Combinations (Continued)

	Ports																			
	E	D	C	B	A	E	D	C	B	A	E	D	C	B	A	E	D	C	B	A
	6K	6K	6K	6K	6K	12K	12K	12K	6K	6K	15K	15K	7K	7K	6K	18K	12K	12K	9K	6K
Five-Zone	7K	6K	6K	6K	6K	12K	12K	12K	7K	6K	15K	15K	7K	7K	7K	18K	12K	12K	9K	7K
	7K	7K	6K	6K	6K	12K	12K	12K	7K	7K	15K	15K	9K	6K	6K	18K	12K	12K	9K	9K
	7K	7K	7K	6K	6K	12K	12K	12K	9K	6K	15K	15K	9K	7K	6K	18K	15K	6K	6K	6K
	7K	7K	7K	7K	6K	12K	12K	12K	9K	7K	15K	15K	9K	7K	7K	18K	15K	7K	6K	6K
	7K	7K	7K	7K	7K	12K	12K	12K	9K	9K	15K	15K	9K	9K	6K	18K	15K	7K	7K	6K
	9K	6K	6K	6K	6K	12K	12K	12K	12K	6K	15K	15K	9K	9K	7K	18K	15K	7K	7K	7K
	9K	7K	6K	6K	6K	12K	12K	12K	12K	7K	15K	15K	9K	9K	9K	18K	15K	9K	6K	6K
	9K	7K	7K	6K	6K	12K	12K	12K	12K	9K	15K	15K	12K	6K	6K	18K	15K	9K	7K	6K
	9K	7K	7K	7K	6K	12K	12K	12K	12K	12K	15K	15K	12K	7K	6K	18K	15K	9K	7K	7K
	9K	7K	7K	7K	7K	15K	6K	6K	6K	6K	15K	15K	12K	7K	7K	18K	15K	9K	9K	6K
	9K	9K	6K	6K	6K	15K	7K	6K	6K	6K	15K	15K	12K	9K	6K	18K	15K	9K	9K	7K
	9K	9K	7K	6K	6K	15K	7K	7K	6K	6K	15K	15K	12K	9K	7K	18K	15K	9K	9K	9K
	9K	9K	7K	7K	6K	15K	7K	7K	7K	6K	15K	15K	12K	9K	9K	18K	15K	12K	6K	6K
	9K	9K	7K	7K	7K	15K	7K	7K	7K	7K	15K	15K	15K	6K	6K	18K	15K	12K	7K	6K
	9K	9K	9K	6K	6K	15K	9K	6K	6K	6K	15K	15K	15K	7K	6K	18K	15K	12K	7K	7K
	9K	9K	9K	7K	6K	15K	9K	7K	6K	6K	15K	15K	15K	7K	7K	18K	15K	12K	9K	6K
	9K	9K	9K	7K	7K	15K	9K	7K	7K	6K	15K	15K	15K	9K	6K	24K	6K	6K	6K	6K
	9K	9K	9K	9K	6K	15K	9K	7K	7K	7K	18K	6K	6K	6K	6K	24K	7K	6K	6K	6K
	9K	9K	9K	9K	7K	15K	9K	9K	6K	6K	18K	7K	6K	6K	6K	24K	7K	7K	6K	6K
	9K	9K	9K	9K	9K	15K	9K	9K	7K	6K	18K	7K	7K	6K	6K	24K	7K	7K	7K	6K
	12K	6K	6K	6K	6K	15K	9K	9K	7K	7K	18K	7K	7K	7K	6K	24K	7K	7K	7K	7K
	12K	7K	6K	6K	6K	15K	9K	9K	9K	6K	18K	7K	7K	7K	7K	24K	9K	6K	6K	6K
	12K	7K	7K	6K	6K	15K	9K	9K	9K	7K	18K	9K	6K	6K	6K	24K	9K	7K	6K	6K
	12K	7K	7K	7K	6K	15K	9K	9K	9K	9K	18K	9K	7K	6K	6K	24K	9K	7K	7K	6K
	12K	7K	7K	7K	7K	15K	12K	6K	6K	6K	18K	9K	7K	7K	6K	24K	9K	7K	7K	7K
	12K	9K	6K	6K	6K	15K	12K	7K	6K	6K	18K	9K	7K	7K	7K	24K	9K	9K	6K	6K
	12K	9K	7K	6K	6K	15K	12K	7K	7K	6K	18K	9K	9K	6K	6K	24K	9K	9K	7K	6K
	12K	9K	7K	7K	6K	15K	12K	7K	7K	7K	18K	9K	9K	7K	6K	24K	9K	9K	7K	7K
	12K	9K	7K	7K	7K	15K	12K	9K	6K	6K	18K	9K	9K	7K	7K	24K	9K	9K	9K	6K
	12K	9K	9K	6K	6K	15K	12K	9K	7K	6K	18K	9K	9K	9K	6K	24K	9K	9K	9K	7K
	12K	9K	9K	7K	6K	15K	12K	9K	7K	7K	18K	9K	9K	9K	7K	24K	9K	9K	9K	9K
	12K	9K	9K	7K	7K	15K	12K	9K	9K	6K	18K	9K	9K	9K	9K	24K	12K	6K	6K	6K
	12K	9K	9K	9K	6K	15K	12K	9K	9K	7K	18K	12K	6K	6K	6K	24K	12K	7K	6K	6K
	12K	9K	9K	9K	7K	15K	12K	9K	9K	9K	18K	12K	7K	6K	6K	24K	12K	7K	7K	6K
	12K	9K	9K	9K	9K	15K	12K	12K	6K	6K	18K	12K	7K	7K	6K	24K	12K	7K	7K	7K
	12K	12K	6K	6K	6K	15K	12K	12K	7K	6K	18K	12K	7K	7K	7K	24K	12K	9K	6K	6K
	12K	12K	7K	6K	6K	15K	12K	12K	7K	7K	18K	12K	9K	6K	6K	24K	12K	9K	7K	6K
	12K	12K	7K	7K	6K	15K	12K	12K	9K	6K	18K	12K	9K	7K	6K	24K	12K	9K	7K	7K
	12K	12K	7K	7K	7K	15K	12K	12K	9K	7K	18K	12K	9K	7K	7K	24K	12K	9K	9K	6K
	12K	12K	9K	6K	6K	15K	12K	12K	9K	9K	18K	12K	9K	9K	6K	24K	15K	6K	6K	6K
	12K	12K	9K	7K	6K	15K	12K	12K	12K	6K	18K	12K	9K	9K	7K	24K	15K	7K	6K	6K
	12K	12K	9K	7K	7K	15K	12K	12K	12K	7K	18K	12K	9K	9K	9K	24K	15K	7K	7K	6K
	12K	12K	9K	9K	6K	15K	12K	12K	12K	9K	18K	12K	12K	6K	6K	24K	15K	7K	7K	7K
	12K	12K	9K	9K	7K	15K	15K	6K	6K	6K	18K	12K	12K	7K	6K	24K	15K	9K	6K	6K
	12K	12K	9K	9K	9K	15K	15K	7K	6K	6K	18K	12K	12K	7K	7K					

Indoor and Outdoor **Compatibility Chart**

Ductless Accessories

An exploded view diagram of the Haier SmartIQ air conditioning unit. The central component is the main outdoor unit, which is white and features a large circular fan grille on the left and the 'Haier SmartIQ' logo on the right. Surrounding this central unit are four other components, each labeled with a blue circle containing a white number: 1. A front panel with a vertical handle, positioned to the left of the main unit. 2. A left side panel, positioned to the left of the front panel. 3. A right side panel with three rectangular cutouts, positioned to the right of the main unit. 4. A top panel, positioned above the main unit.

Operating Conditions	Recommended Accessories			
	1 Front Wind Baffle	2 Side Wind Baffle	3 Back Wind Baffle	4 Top Cover
Low Ambient Cooling below 23°F (5°C) (server/mechanical room)	Required	Required	Required	Required
Low Ambient Heating below 5°F (-15°C)	-	Strongly Recommended	Strongly Recommended	Strongly Recommended
Unit installed on a flat roof or facing prevailing wind	Required	-	-	-

A front wind baffle is required for all climates when mounted on a flat roof or facing prevailing winds.

Outdoor Unit Accessory Compatibility Table

[illegible]

Cassette Panels

Remote controller (WJ26X35394) is included with 4-way cassette panel.

Remote controller (WJ26X35393) is included with one-way cassette panel.



QACCP01WA

4-Way Compact
Cassette Panel

Fits Models:
US09CB2BEA
US12CB2BEA
US18CB2BEA



QALCP01WA

4-Way Large
Cassette Panel

Fits Models:
US24LB2BEA
US30LB2BEA
US36LB2BEA




QAABP0718A

One-Way Cassette Panel

Fits Models:
US07AB2BEA
US09AB2BEA
US12AB2BEA
US18AB2BEA


Supply Plenums

Supply plenums for ducted indoor models.




UAPT0912A

Fits Models:
US09MB2BEA
US12MB2BEA



UAPT1824A

Fits Models:
US18MB2BEA
US24MB2BEA



UAPT3048A

Fits Models:
US30MB2BEA
US36MB2BEA
US42MB2BEA
US48MB2BEA

Refrigerant Detection Sensor (RDS)




UALS01A

Ductless Refrigerant
Detection Sensor

Note: See room sizing requirements to determine if the Refrigerant Detection Sensor (RDS) is required and needs to be purchased separately for highwall and cassette indoor units. RDS is factory-installed on 6K and 9K-24K (models ending in "B") premium highwalls, console, and ducted units.

Merv Return Air Filter Boxes

MERV return air filter boxes for ducted indoor models.



UAMFB0912A

Fits Models:
US09MB2BEA
US12MB2BEA

UAMFB1824A

Fits Models:
US18MB2BEA
US24MB2BEA


UAMFB3048A

Fits Models:
US30MB2BEA
US36MB2BEA
US42MB2BEA
US48MB2BEA

Controllers

Controllers from Haier allow you to take command of your environment. With convenient user-friendly button layouts and clear digital displays, the system can be easily set to meet and maintain comfort levels.

Wired Controller



Compatible with all indoor unit types.

	QACT17B
Power Supply	12V AC
Controllable Indoor Groups	Up to 16
On/Off	•
Modes	Auto-Cool-Dry-Heat-Fan-Auto
Precise Temperature Control +/- 1°F (+/- 0.5°C)	•
Fan Speed Adjustment	•
Turbo	•
Quiet	•
Airflow Direction - Up/Down	•
Airflow Direction - Left/Right	•
Four-Way Cassette Blade Control	
Indoor Temperature Display	•
Filter Change Reminder	500 hr
Clock	
Error Code Reporting/ Recording	•
Control Lock	•
Daily Program	
Weekly Program	
Sleep	
Backlight	•
Fahrenheit/Celsius Display	•
Temperature Range Limit	•
Temperature Compensation	•
Static Pressure Setting	•
Groups Setting	•
Password	

Remote Controllers



Ships with standard highwalls & one-way cassette panels.



Ships with consoles.



Ships with premium highwalls & 4-way cassette panels.

	WJ26X35393	WJ26X35813	WJ26X35394
Individual Control	•	•	•
Backlight	•	•	•
Up/Down Louver Oscillating Control	•	•	•
Left/Right Louver Oscillating Control			•
Four-Way Cassette Air Supply Control			•
Child Lock	•	•	•
Indoor LED Display On/Off	•	•	•
Fahrenheit/Celsius Display	•	•	•
Precise Temperature Control +/- 1°F (+/- 0.5°C)	•	•	•
Motion Sensor			•

5" Central Controller

5" LED Touch Screen

A vibrant and intuitive interface for easy navigation and control.

Integration Capability

Seamlessly integrates both ductless and central HVAC systems for unified management.

Multi-Zone Control

Manages up to 31 ductless zones and 1 central 24V HVAC zone, providing comprehensive climate control.



	UACT32A
Screen Saving	•
Backlight	•
Power Supply	24VAC*
Max. IDUs Controllable	31 + (1) 24VAC Central Zone
Indoor/Set-Point Temperature Display	•
Interlock Input	•
Interlock Output Dry Contact	•
Temperature Set Range	60-86°F (16-30°C)
Zones	Up to 31 Zones
Modes	Cool, Heat, Auto, Dry, Fan
Fan Speeds	Low, Med, High
Group Control	•
Individual IDU Control	•
Dual System Rotational Operation	•
Temperature Set Range	40-99°F (5-37°C)
Humidity	Display in %
Mode	Cool, Heat, Auto
Fan Speed	Auto, Circulating, On
WiFi/Alexa/Google Home	•

*if not connecting to 24V central HVAC system, a field supplied 24VAC transformer is needed.

Indoor Unit Accessory Compatibility Table

		Remote Controllers			Wired Controller	Refrigerant Detection Sensor (RDS)
						
	Model Number	WJ26X35393	WJ26X35813	WJ26X35394	QACT17B	UALS01A
Caliber 115V Highwall	QS09WB1BEA	●			○	○
	QS12WB1BEA	●			○	○
Standard Highwall	QS07WB2BEA	●			○	○
	QS09WB2BEA	●			○	○
	QS12WB2BEA	●			○	○
	QS15WB2BEA	●			○	○
	QS18WB2BEA	●			○	○
	QS24WB2BEA	●			○	○
	QS30WB2BEA	●			○	○
	QS36WB2BEA	●			○	○
Premium Highwall	QS06WP2BEA			●	○	●
	QS09WP2BEA			●	○	○
	QS09WP2BEB			●	○	●
	QS12WP2BEA			●	○	○
	QS12WP2BEB			●	○	●
	QS18WP2BEA			●	○	○
	QS18WP2BEB			●	○	●
	QS24WP2BEA			●	○	○
4-Way Compact Cassette	QS24WP2BEB			●	○	●
	US09CB2BEA					○
	US12CB2BEA					○
	US18CB2BEA					○
4-Way Large Cassette	QACCP01WA*			●	○	
	US24LB2BEA					○
	US30LB2BEA					○
	US36LB2BEA					○
One-Way Cassette	QALCP01WA*			●	○	
	US07AB2BEA					○
	US09AB2BEA					○
	US12AB2BEA					○
	US18AB2BEA					○
Console	QAABP0718A*	●			○	
	US09FB2BEA		●		○	●
	US12FB2BEA		●		○	●
Mid-Static Ducted	US18FB2BEA		●		○	●
	US09MB2BEA				⊙	●
	US12MB2BEA				⊙	●
	US18MB2BEA				⊙	●
	US24MB2BEA				⊙	●
	US30MB2BEA				⊙	●
	US36MB2BEA				⊙	●
	US42MB2BEA				⊙	●
	US48MB2BEA				⊙	●

*Cassette Panel


● = Included ⊙ = Required, sold separately ○ = Optional; sold separately

See Outdoor Unit Accessory Compatibility Table for 5" Central Controller compatibility

Quick Reference Guide

Model Number **Nomenclature**


Ductless Outdoor Unit Nomenclature



EXAMPLES:

1Q12TE2BEA: Haier 12K Tempo Single Zone

Ductless Indoor Unit Nomenclature



EXAMPLES:

QS09WB2BEA: Haier 9K Standard Highwall

US12MB2BEA: Universal 12K Ducted



Haier



LIMITED WARRANTY

We take pride in our workmanship; our standard coverage includes a 5-year limited warranty on parts.

Additionally, our ductless systems qualify for a 10-year limited warranty on parts with registration. To receive the extended coverage, equipment must be registered within 60 days of installation. Please refer to the warranty documentation for complete details.



To register your equipment go to:
www.geappliancesairandwater.com/warranty



GE APPLIANCES
a Haier company

AIR&WATER
SOLUTIONS

